


<b>TEST REPORT</b> <b>IEC/EN 60950-1</b> <b>Safety of information technology equipment</b> <b>Part 1-General requirements</b>	
Report reference No .....	R2DG171102009-03
Compiled by (+ signature) .....	Test Engineer: Acan Liang <i>Acan Liang</i>
Approved by (+ signature) .....	Team Leader: Robin He <i>Robin He</i>
Date of issue .....	2017-11-27
Testing laboratory .....	Bay Area Compliance Laboratories Corp. (Dongguan)
Address .....	No.69, Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China
Testing location .....	As above
Applicant's name .....	SHENZHEN TENDA TECHNOLOGY CO.,LTD.
Address .....	6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052
Manufacturer's name.....	Same as applicant
Address .....	Same as applicant
Factory's name .....	N/A
Address .....	N/A
Standard .....	EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013; IEC 60950-1:2005+A1:2009+A2:2013
Test sample(s) received .....	2017-11-08
Test in period.....	2017-11-09 to 2017-11-24
Procedure deviation .....	N/A
Non-standard test method .....	N/A
Note: The test data was only valid for the test sample(s). This test report is prepared for the customer shown above and for the specific product described herein. It must not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).	

Test item description .....: AC1200 MU-MIMO Dual Band Gigabit WiFi Router  
 Trademark .....: Tenda  
 Model/type reference .....: AC10  
 Manufacturer .....: Same as applicant  
 Rating .....: EUT input: 12V  $\approx$  1.0A

Copy of marking plate:  
 The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



- Note:
- The CE marking and WEEE symbol (if any) should be at least 5,0mm and 7,0mm respectively in height.
  - Manufacturers shall ensure that the equipment bears a type, batch or serial number or other element allowing its identification.
  - Manufacturers shall indicate on the electrical equipment their name, registered trade name or registered trade mark and the postal address at which they can be contacted.
  - Importers shall indicate on the electrical equipment their name, registered trade name or registered trade mark and the postal address at which they can be contacted.

<b>Test item particulars</b> .....	
Equipment mobility .....	<input checked="" type="checkbox"/> movable <input type="checkbox"/> hand-held <input type="checkbox"/> transportable <input type="checkbox"/> stationary <input type="checkbox"/> for building-in <input type="checkbox"/> direct plug-in
Connection to the mains.....	<input type="checkbox"/> pluggable equipment <input type="checkbox"/> type A <input type="checkbox"/> type B <input type="checkbox"/> detachable power supply cord <input type="checkbox"/> non-detachable power supply cord <input type="checkbox"/> permanent connection <input checked="" type="checkbox"/> not directly connected to the mains
Operating condition .....	<input checked="" type="checkbox"/> continuous <input type="checkbox"/> rated operating / resting time:
Access location .....	<input checked="" type="checkbox"/> operator accessible <input type="checkbox"/> restricted access location
Over voltage category (OVC) .....	<input type="checkbox"/> OVC I <input type="checkbox"/> OVC II <input type="checkbox"/> OVC III <input type="checkbox"/> OVC IV <input checked="" type="checkbox"/> other: supplied by SELV circuits
Mains supply tolerance (%) .....	N/A
Tested for IT power systems .....	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
IT testing, phase-phase voltage (V) .....	N/A
Class of equipment .....	<input type="checkbox"/> Class I <input type="checkbox"/> Class II <input checked="" type="checkbox"/> Class III <input type="checkbox"/> Not classified
Considered current rating of protective device as part of the building installation (A) .....	N/A
Pollution degree (PD) .....	<input type="checkbox"/> PD 1 <input checked="" type="checkbox"/> PD 2 <input type="checkbox"/> PD 3
IP protection class .....	IPX0
Altitude during operation (m) .....	Up to 2000m
Altitude of test laboratory (m) .....	Below 2000m
Max. Specified ambient temperature(°C) .....	40°C
Mass of equipment (kg).....	Approx. 0.35kg
<b>Possible test case verdicts</b> .....	
- test case does not apply to the test object.....	N/A(or N)
- test object does meet the requirement.....	P(ass)
- test object does not meet the requirement.....	F(ail)
<b>General remarks:</b>	
<p>”(see remark #)” refers to a remark appended to the report.          (see appended table)” refers to a table appended to the report.          The test results presented in this report relate only to the object tested.          This report shall not be reproduced, except in full, without the written approval of the testing laboratory.          Throughout this report a <input type="checkbox"/>comma/ <input checked="" type="checkbox"/>point is used as the decimal separator.</p>	

**Summary of testing:**

All tests were performed at the worst case and all test results complied with the standard on the cover page.

**General product information:**

1. The product is an AC1200 MU-MIMO Dual Band Gigabit WiFi Router designed as information technology equipment, for indoor use only.
2. The product is supplied by a 12VDC SELV circuit of external power supply, which complied with the requirements of clause 2.5 limited power sources.
3. The test samples are pre-production samples without serial numbers.
4. Before placing the products in the different countries, the manufacturer must ensure that: Operating Instructions, Ratings Labels and Warnings Labels are in an Accepted or Official Language of the country in question; The equipment complies with the National Standards and/or Electrical Codes of the country, province or city or in question.

F E M N A L

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
<b>1</b>	<b>General</b>		<b>P</b>
<b>1.5</b>	<b>Components</b>		<b>P</b>
1.5.1	General	Components that were found to affect safety aspects comply with the requirements of this standard or within the safety aspects of the relevant IEC component standards.	P
	Comply with IEC 60950-1 or relevant component standard	(see appended table 1.5.1)	P
1.5.2	Evaluation and testing of components	<p>Certified components are used in accordance with their ratings, certifications and they comply with applicable parts of this Standard.</p> <p>Components not certified are used in accordance with their ratings and they comply with IEC 60950-1 and the relevant component Standard.</p> <p>Components, for which no relevant IEC Standard exist, have been tested under the condition occurring in the equipment, using applicable parts of IEC 60950-1.</p>	P
1.5.3	Thermal controls	No thermal controls	N/A
1.5.4	Transformers	No transformer used.	N/A
1.5.5	Interconnecting cables	Comply with this standard.	P
1.5.6	Capacitors bridging insulation		N/A
1.5.7	Resistors bridging insulation		N/A
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		N/A
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits		N/A
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable		N/A
1.5.8	Components in equipment for IT power systems		N/A
1.5.9	Surge suppressors		N/A
1.5.9.1	General		N/A
1.5.9.2	Protection of VDRs		N/A
1.5.9.3	Bridging of functional insulation by a VDR		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.5.9.4	Bridging of basic insulation by a VDR		N/A
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		N/A

<b>1.6</b>	<b>Power interface</b>		<b>P</b>
1.6.1	AC power distribution systems	Class III equipment	N/A
1.6.2	Input current	(see appended table 1.6.2)	P
1.6.3	Voltage limit of hand-held equipment	Not hand-held equipment	N/A
1.6.4	Neutral conductor		N/A

<b>1.7</b>	<b>Marking and instructions</b>		<b>P</b>
1.7.1	Power rating and identification markings	See below	P
1.7.1.1	Power rating marking	See below	P
	Multiple mains supply connections.....:		N/A
	Rated voltage(s) or voltage range(s) (V) .....	12V	P
	Symbol for nature of supply, for d.c. only .....	==	P
	Rated frequency or rated frequency range (Hz) .....		N/A
	Rated current (mA or A) .....	1.0A	P
1.7.1.2	Identification markings	See below	P
	Manufacturer's name or trade-mark or identification mark .....	See marking plate	P
	Model identification or type reference .....	See marking plate	P
	Symbol for Class II equipment only .....	Class III equipment	N/A
	Other markings and symbols .....	Others marking can be added, which not misunderstand.	P
1.7.2	Safety instructions and marking	In user manual	P
1.7.2.1	General	Considered.	P
1.7.2.2	Disconnect devices	Class III equipment	N/A
	-for permanently connected equipment, a readily accessible disconnect device shall be incorporated in the building installation wiring		N/A
	-for pluggable equipment, the socket-outlet shall be installed near the equipment and shall be easily accessible		N/A
1.7.2.3	Overcurrent protective device		N/A
1.7.2.4	IT power distribution systems		N/A
1.7.2.5	Operator access with a tool		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.2.6	Ozone	The equipment does not produce ozone.	N/A
1.7.3	Short duty cycles	The equipment is intended for continuous operation.	N/A
1.7.4	Supply voltage adjustment .....	No voltage select switch.	N/A
	Methods and means of adjustment; reference to installation instructions .....		N/A
1.7.5	Power outlets on the equipment .....	No such device.	N/A
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference) .....	No such component.	N/A
1.7.7	Wiring terminals	No such wiring terminals.	N/A
1.7.7.1	Protective earthing and bonding terminals .....	No such terminals.	N/A
1.7.7.2	Terminals for a.c. mains supply conductors	No connection to mains supply.	N/A
1.7.7.3	Terminals for d.c. mains supply conductors	No connection to mains supply.	N/A
1.7.8	Controls and indicators	Safety is not involved	N/A
1.7.8.1	Identification, location and marking .....		N/A
1.7.8.2	Colours .....		N/A
1.7.8.3	Symbols according to IEC 60417 .....		N/A
1.7.8.4	Markings using figures .....		N/A
1.7.9	Isolation of multiple power sources .....		N/A
1.7.10	Thermostats and other regulating devices .....		N/A
1.7.11	Durability	Rubbed with a cloth soaked with water for 15s then again for 15s with cloth soaked with petroleum spirit, after this test, the marking on the label did not fade there are no curling nor lifting of the label edge.	P
1.7.12	Removable parts	No removable parts	N/A
1.7.13	Replaceable batteries .....	No batteries	N/A
	Language(s) .....		—
1.7.14	Equipment for restricted access locations.....		N/A

<b>2</b>	<b>Protection from hazards</b>		<b>P</b>
2.1	Protection from electric shock and energy hazards		P
2.1.1	Protection in operator access areas	Supplied by SELV circuits	P
2.1.1.1	Access to energized parts		N/A
	Test by inspection .....		N/A
	Test with test finger (Figure 2A) .....		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Test with test pin (Figure 2B) .....		N/A
	Test with test probe (Figure 2C) .....	No TNV circuits.	N/A
2.1.1.2	Battery compartments	No such component	N/A
2.1.1.3	Access to ELV wiring	No ELV wiring	N/A
	Working voltage (V <sub>peak</sub> or V <sub>rms</sub> ); minimum distance through insulation (mm)		—
2.1.1.4	Access to hazardous voltage circuit wiring	No hazardous voltage circuit wiring	N/A
2.1.1.5	Energy hazards .....	(See appended table 2.1.1.5)	P
2.1.1.6	Manual controls	No such device	N/A
2.1.1.7	Discharge of capacitors in equipment	No such component	N/A
	Measured voltage (V); time-constant (s) .....		—
2.1.1.8	Energy hazards – d.c. mains supply	No connection to mains supply	N/A
	a) Capacitor connected to the d.c. mains supply ..:		N/A
	b) Internal battery connected to the d.c. mains supply .....		N/A
2.1.1.9	Audio amplifiers .....	No Audio amplifiers provided	N/A
2.1.2	Protection in service access areas		N/A
2.1.3	Protection in restricted access locations		N/A

<b>2.2</b>	<b>SELV circuits</b>		<b>P</b>
2.2.1	General requirements	Class III equipment.	P
2.2.2	Voltages under normal conditions (V) .....	Less than 42.4V peak or 60V d.c., not exceeded in SELV circuits.	P
2.2.3	Voltages under fault conditions (V) .....	Not exceed 42.4V peak or 60V d.c. for longer than 0.2s, and under limit of 71V peak or 120V d.c. within 0.2s.	P
2.2.4	Connection of SELV circuits to other circuits .....	Only connection to SELV circuit.	P

<b>2.3</b>	<b>TNV circuits</b>		<b>N/A</b>
2.3.1	Limits	No TNV circuits.	N/A
	Type of TNV circuits .....		—
2.3.2	Separation from other circuits and from accessible parts		N/A
2.3.2.1	General requirements		N/A
2.3.2.2	Protection by basic insulation		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.3.2.3	Protection by earthing		N/A
2.3.2.4	Protection by other constructions .....		N/A
2.3.3	Separation from hazardous voltages		N/A
	Insulation employed.....		—
2.3.4	Connection of TNV circuits to other circuits		N/A
	Insulation employed.....		—
2.3.5	Test for operating voltages generated externally		N/A
<b>2.4</b>	<b>Limited current circuits</b>		<b>N/A</b>
2.4.1	General requirements	No limited current circuit.	N/A
2.4.2	Limit values		N/A
	Frequency (Hz).....		—
	Measured current (mA).....		—
	Measured voltage (V) .....		—
	Measured circuit capacitance (nF or $\mu$ F).....		—
2.4.3	Connection of limited current circuits to other circuits		N/A
<b>2.5</b>	<b>Limited power sources</b>		<b>P</b>
	a) Inherently limited output		N/A
	b) Impedance limited output		N/A
	c) Regulating network limited output under normal operating and single fault condition	LAN Ports	P
	d) Overcurrent protective device limited output		N/A
	Max. output voltage (V), max. output current (A), max. apparent power (VA) .....	(see appended table 2.5)	—
	Current rating of overcurrent protective device (A)		—
	Use of integrated circuit (IC) current limiters		N/A
<b>2.6</b>	<b>Provisions for earthing and bonding</b>		<b>N/A</b>
2.6.1	Protective earthing	Class III equipment	N/A
2.6.2	Functional earthing		N/A
2.6.3	Protective earthing and protective bonding conductors		N/A
2.6.3.1	General		N/A
2.6.3.2	Size of protective earthing conductors		N/A
	Rated current (A), cross-sectional area ( $\text{mm}^2$ ), AWG .....		—

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.6.3.3	Size of protective bonding conductors		N/A
	Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....		—
2.6.3.4	Resistance of earthing conductors and their terminations; resistance (Ω), voltage drop (V), test current (A), duration (min) .....		N/A
2.6.3.5	Colour of insulation .....		N/A
2.6.4	Terminals		N/A
2.6.4.1	General		N/A
2.6.4.2	Protective earthing and bonding terminals		N/A
	Rated current (A), type, nominal thread diameter (mm) .....		—
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors		N/A
2.6.5	Integrity of protective earthing		N/A
2.6.5.1	Interconnection of equipment		N/A
2.6.5.2	Components in protective earthing conductors and protective bonding conductors		N/A
2.6.5.3	Disconnection of protective earth		N/A
2.6.5.4	Parts that can be removed by an operator		N/A
2.6.5.5	Parts removed during servicing		N/A
2.6.5.6	Corrosion resistance		N/A
2.6.5.7	Screws for protective bonding		N/A
2.6.5.8	Reliance on telecommunication network or cable distribution system		N/A

<b>2.7</b>	<b>Overcurrent and earth fault protection in primary circuits</b>		<b>N/A</b>
2.7.1	Basic requirements	Class III equipment	N/A
	Instructions when protection relies on building installation		N/A
2.7.2	Faults not simulated in 5.3.7		N/A
2.7.3	Short-circuit backup protection		N/A
2.7.4	Number and location of protective devices .....		N/A
2.7.5	Protection by several devices		N/A
2.7.6	Warning to service personnel .....		N/A

<b>2.8</b>	<b>Safety interlocks</b>		<b>N/A</b>
2.8.1	General principles	No safety interlocks	N/A
2.8.2	Protection requirements		N/A
2.8.3	Inadvertent reactivation		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.8.4	Fail-safe operation		N/A
	Protection against extreme hazard		N/A
2.8.5	Moving parts		N/A
2.8.6	Overriding		N/A
2.8.7	Switches, relays and their related circuits		N/A
2.8.7.1	Separation distances for contact gaps and their related circuits (mm) .....		N/A
2.8.7.2	Overload test		N/A
2.8.7.3	Endurance test		N/A
2.8.7.4	Electric strength test		N/A
2.8.8	Mechanical actuators		N/A

<b>2.9</b>	<b>Electrical insulation</b>		<b>N/A</b>
2.9.1	Properties of insulating materials		N/A
2.9.2	Humidity conditioning		N/A
	Relative humidity (%), temperature (°C) .....		—
2.9.3	Grade of insulation		N/A
2.9.4	Separation from hazardous voltages		N/A
	Method(s) used .....		—

<b>2.10</b>	<b>Clearances, creepage distances and distances through insulation</b>		<b>N/A</b>
2.10.1	General	Class III equipment	N/A
2.10.1.1	Frequency .....		N/A
2.10.1.2	Pollution degrees .....		N/A
2.10.1.3	Reduced values for functional insulation		N/A
2.10.1.4	Intervening unconnected conductive parts		N/A
2.10.1.5	Insulation with varying dimensions		N/A
2.10.1.6	Special separation requirements		N/A
2.10.1.7	Insulation in circuits generating starting pulses		N/A
2.10.2	Determination of working voltage		N/A
2.10.2.1	General		N/A
2.10.2.2	RMS working voltage		N/A
2.10.2.3	Peak working voltage		N/A
2.10.3	Clearances		N/A
2.10.3.1	General		N/A
2.10.3.2	Mains transient voltages		N/A
	a) AC mains supply .....		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	b) Earthed d.c. mains supplies .....		N/A
	c) Unearthed d.c. mains supplies .....		N/A
	d) Battery operation .....		N/A
2.10.3.3	Clearances in primary circuits		N/A
2.10.3.4	Clearances in secondary circuits		N/A
2.10.3.5	Clearances in circuits having starting pulses		N/A
2.10.3.6	Transients from a.c. mains supply .....		N/A
2.10.3.7	Transients from d.c. mains supply .....		N/A
2.10.3.8	Transients from telecommunication networks and cable distribution systems .....		N/A
2.10.3.9	Measurement of transient voltage levels		N/A
	a) Transients from a mains supply		N/A
	For an a.c. mains supply .....		N/A
	For a d.c. mains supply .....		N/A
	b) Transients from a telecommunication network :		N/A
2.10.4	Creepage distances		N/A
2.10.4.1	General		N/A
2.10.4.2	Material group and comparative tracking index		N/A
	CTI tests .....		—
2.10.4.3	Minimum creepage distances		N/A
2.10.5	Solid insulation		N/A
2.10.5.1	General		N/A
2.10.5.2	Distances through insulation		N/A
2.10.5.3	Insulating compound as solid insulation		N/A
2.10.5.4	Semiconductor devices		N/A
2.10.5.5	Cemented joints		N/A
2.10.5.6	Thin sheet material – General		N/A
2.10.5.7	Separable thin sheet material		N/A
	Number of layers (pcs) .....		—
2.10.5.8	Non-separable thin sheet material		N/A
2.10.5.9	Thin sheet material – standard test procedure		N/A
	Electric strength test		—
2.10.5.10	Thin sheet material – alternative test procedure		N/A
	Electric strength test		—
2.10.5.11	Insulation in wound components		N/A
2.10.5.12	Wire in wound components		N/A
	Working voltage .....		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	a) Basic insulation not under stress .....		N/A
	b) Basic, supplementary, reinforced insulation .....		N/A
	c) Compliance with Annex U .....		N/A
	Two wires in contact inside wound component; angle between 45° and 90° .....		N/A
2.10.5.13	Wire with solvent-based enamel in wound components		N/A
	Electric strength test		—
	Routine test		N/A
2.10.5.14	Additional insulation in wound components		N/A
	Working voltage .....		N/A
	- Basic insulation not under stress .....		N/A
	- Supplementary, reinforced insulation .....		N/A
2.10.6	Construction of printed boards		N/A
2.10.6.1	Uncoated printed boards		N/A
2.10.6.2	Coated printed boards		N/A
2.10.6.3	Insulation between conductors on the same inner surface of a printed board		N/A
2.10.6.4	Insulation between conductors on different layers of a printed board		N/A
	Distance through insulation		N/A
	Number of insulation layers (pcs).....		N/A
2.10.7	Component external terminations		N/A
2.10.8	Tests on coated printed boards and coated components		N/A
2.10.8.1	Sample preparation and preliminary inspection		N/A
2.10.8.2	Thermal conditioning		N/A
2.10.8.3	Electric strength test		N/A
2.10.8.4	Abrasion resistance test		N/A
2.10.9	Thermal cycling		N/A
2.10.10	Test for Pollution Degree 1 environment and insulating compound		N/A
2.10.11	Tests for semiconductor devices and cemented joints		N/A
2.10.12	Enclosed and sealed parts		N/A
<b>3</b>	<b>Wiring, connections and supply</b>		<b>P</b>
3.1	General		P

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
3.1.1	Current rating and overcurrent protection	The cross-sectional area of internal wires and interconnecting cables be adequate for the current they are intended to carry when the equipment is operating under normal load such that the maximum permitted temperature of conductor insulation is not exceeded.	P
3.1.2	Protection against mechanical damage	Wireways are smooth and free from sharp edges.	P
3.1.3	Securing of internal wiring	The wires are positioned in such a manner that prevents excessive strain, loosening of terminal connections and damage of conductor insulation.	P
3.1.4	Insulation of conductors		N/A
3.1.5	Beads and ceramic insulators	No beads or similar ceramic insulators on conductors.	N/A
3.1.6	Screws for electrical contact pressure	No screw for electrical contact	N/A
3.1.7	Insulating materials in electrical connections	No contact pressure through insulating material.	N/A
3.1.8	Self-tapping and spaced thread screws	Thread-cutting or space thread screws are not used for electrical connections.	N/A
3.1.9	Termination of conductors		N/A
	10 N pull test		N/A
3.1.10	Sleeving on wiring	No such sleeving.	N/A

<b>3.2</b>	<b>Connection to a mains supply</b>		<b>N/A</b>
3.2.1	Means of connection	Class III equipment	N/A
3.2.1.1	Connection to an a.c. mains supply		N/A
3.2.1.2	Connection to a d.c. mains supply		N/A
3.2.2	Multiple supply connections		N/A
3.2.3	Permanently connected equipment		N/A
	Number of conductors, diameter of cable and conduits (mm) .....		—
3.2.4	Appliance inlets		N/A
3.2.5	Power supply cords		N/A
3.2.5.1	AC power supply cords		N/A
	Type .....		—

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....		—
3.2.5.2	DC power supply cords		N/A
3.2.6	Cord anchorages and strain relief		N/A
	Mass of equipment (kg), pull (N) .....		—
	Longitudinal displacement (mm) .....		—
3.2.7	Protection against mechanical damage		N/A
3.2.8	Cord guards		N/A
	Diameter or minor dimension D (mm); test mass (g) .....		—
	Radius of curvature of cord (mm).....		—
3.2.9	Supply wiring space		N/A

<b>3.3</b>	<b>Wiring terminals for connection of external conductors</b>		<b>N/A</b>
3.3.1	Wiring terminals	No such terminal	N/A
3.3.2	Connection of non-detachable power supply cords		N/A
3.3.3	Screw terminals		N/A
3.3.4	Conductor sizes to be connected		N/A
	Rated current (A), cord/cable type, cross-sectional area (mm <sup>2</sup> ).....		—
3.3.5	Wiring terminal sizes		N/A
	Rated current (A), type, nominal thread diameter (mm) .....		—
3.3.6	Wiring terminal design		N/A
3.3.7	Grouping of wiring terminals		N/A
3.3.8	Stranded wire		N/A

<b>3.4</b>	<b>Disconnection from the mains supply</b>		<b>N/A</b>
3.4.1	General requirement	Class III equipment	N/A
3.4.2	Disconnect devices		N/A
3.4.3	Permanently connected equipment		N/A
3.4.4	Parts which remain energized		N/A
3.4.5	Switches in flexible cords		N/A
3.4.6	Number of poles - single-phase and d.c. equipment		N/A
3.4.7	Number of poles - three-phase equipment		N/A
3.4.8	Switches as disconnect devices		N/A
3.4.9	Plugs as disconnect devices		N/A
3.4.10	Interconnected equipment		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

3.4.11	Multiple power sources		N/A
--------	------------------------	--	-----

<b>3.5</b>	<b>Interconnection of equipment</b>		<b>P</b>
3.5.1	General requirements	Considered.	P
3.5.2	Types of interconnection circuits .....	SELV circuits.	P
3.5.3	ELV circuits as interconnection circuits	No ELV circuits	N/A
3.5.4	Data ports for additional equipment	(See appended table 2.5)	P

<b>4</b>	<b>Physical requirements</b>		<b>P</b>
4.1	Stability		N/A
	Angle of 10°	Mass < 7kg	N/A
	Test force (N) .....	The unit is not floor-standing equipment.	N/A

<b>4.2</b>	<b>Mechanical strength</b>		<b>N/A</b>
4.2.1	General	See below.	N/A
	Rack-mounted equipment.	Not rack-mounted equipment.	N/A
4.2.2	Steady force test, 10 N	Class III equipment.	N/A
4.2.3	Steady force test, 30 N		N/A
4.2.4	Steady force test, 250 N	After test, no hazard.	N/A
4.2.5	Impact test	Class III equipment.	N/A
	Fall test	Class III equipment.	N/A
	Swing test	Class III equipment.	N/A
4.2.6	Drop test; height (mm) .....		N/A
4.2.7	Stress relief test	Class III equipment.	N/A
4.2.8	Cathode ray tubes	CRT(s) not used in the equipment.	N/A
	Picture tube separately certified .....		N/A
4.2.9	High pressure lamps	No high pressure lamps in the equipment.	N/A
4.2.10	Wall or ceiling mounted equipment; force (N) .....		N/A

<b>4.3</b>	<b>Design and construction</b>		<b>P</b>
4.3.1	Edges and corners	Edges and corners of the enclosure are rounded.	P
4.3.2	Handles and manual controls; force (N).....	No such device	N/A
4.3.3	Adjustable controls	No such device	N/A
4.3.4	Securing of parts		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.3.5	Connection by plugs and sockets		N/A
4.3.6	Direct plug-in equipment		N/A
	Torque .....		—
	Compliance with the relevant mains plug standard .....		N/A
4.3.7	Heating elements in earthed equipment	No such component	N/A
4.3.8	Batteries	No batteries	N/A
	- Overcharging of a rechargeable battery		N/A
	- Unintentional charging of a non-rechargeable battery		N/A
	- Reverse charging of a rechargeable battery		N/A
	- Excessive discharging rate for any battery		N/A
4.3.9	Oil and grease	No oil and greases.	N/A
4.3.10	Dust, powders, liquids and gases		N/A
4.3.11	Containers for liquids or gases		N/A
4.3.12	Flammable liquids .....		N/A
	Quantity of liquid (l) .....		N/A
	Flash point (°C) .....		N/A
4.3.13	Radiation	Considered	P
4.3.13.1	General	See below	P
4.3.13.2	Ionizing radiation		N/A
	Measured radiation (pA/kg) .....		—
	Measured high-voltage (kV) .....		—
	Measured focus voltage (kV) .....		—
	CRT markings .....		—
4.3.13.3	Effect of ultraviolet (UV) radiation on materials		N/A
	Part, property, retention after test, flammability classification .....		N/A
4.3.13.4	Human exposure to ultraviolet (UV) radiation .....		N/A
4.3.13.5	Lasers (including laser diodes) and LEDs	LEDs used as indicator	P
4.3.13.5.1	Lasers (including laser diodes)		N/A
	Laser class .....		—
4.3.13.5.2	Light emitting diodes (LEDs)	LEDs used as indicator	P
4.3.13.6	Other types .....		N/A
<b>4.4</b>	<b>Protection against hazardous moving parts</b>		<b>N/A</b>
4.4.1	General	No moving parts	N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.4.2	Protection in operator access areas .....		N/A
	Household and home/office document/media shredders		N/A
4.4.3	Protection in restricted access locations .....		N/A
4.4.4	Protection in service access areas		N/A
4.4.5	Protection against moving fan blades		N/A
4.4.5.1	General		N/A
	Not considered to cause pain or injury. a) .....		N/A
	Is considered to cause pain, not injury. b) .....		N/A
	Considered to cause injury. c) .....		N/A
4.4.5.2	Protection for users		N/A
	Use of symbol or warning .....		N/A
4.4.5.3	Protection for service persons		N/A
	Use of symbol or warning .....		N/A

<b>4.5</b>	<b>Thermal requirements</b>		<b>P</b>
4.5.1	General	See below	P
4.5.2	Temperature tests	(see appended table 4.5)	P
	Normal load condition per Annex L .....	See appended table 1.6.2	—
4.5.3	Temperature limits for materials	(see appended table 4.5)	P
4.5.4	Touch temperature limits	(see appended table 4.5)	P
4.5.5	Resistance to abnormal heat .....		—

<b>4.6</b>	<b>Openings in enclosures</b>		<b>P</b>
4.6.1	Top and side openings		P
	Dimensions (mm) .....	No hazards when the objects enter the openings	—
4.6.2	Bottoms of fire enclosures	No fire enclosure needed	N/A
	Construction of the bottom, dimensions (mm) ...:		—
4.6.3	Doors or covers in fire enclosures		N/A
4.6.4	Openings in transportable equipment		N/A
4.6.4.1	Constructional design measures		N/A
	Dimensions (mm) .....		—
4.6.4.2	Evaluation measures for larger openings		N/A
4.6.4.3	Use of metallized parts		N/A
4.6.5	Adhesives for constructional purposes		N/A
	Conditioning temperature (°C), time (weeks).....:		—

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
<b>4.7</b>	<b>Resistance to fire</b>		<b>P</b>
4.7.1	Reducing the risk of ignition and spread of flame	Method 1 used. See below.	P
	Method 1, selection and application of components wiring and materials	Materials with the required flammability classes are used-see appended table 1.5.1	P
	Method 2, application of all of simulated fault condition tests		N/A
4.7.2	Conditions for a fire enclosure	See below	P
4.7.2.1	Parts requiring a fire enclosure		N/A
4.7.2.2	Parts not requiring a fire enclosure	All the components mounted on rated min. V-1 PCB and supplied by an approved adapter with LPS. No need fire enclosure.	P
4.7.3	Materials	All the components mounted on rated min. V-1 PCB and supplied by an approved adapter with LPS. No need fire enclosure.	P
4.7.3.1	General	All the components mounted on rated min. V-1 PCB and supplied by an approved adapter with LPS. No need fire enclosure.	P
4.7.3.2	Materials for fire enclosures	No fire enclosure needed	N/A
4.7.3.3	Materials for components and other parts outside fire enclosures		N/A
4.7.3.4	Materials for components and other parts inside fire enclosures		N/A
4.7.3.5	Materials for air filter assemblies	No air filter assemblies	N/A
4.7.3.6	Materials used in high-voltage components	No high-voltage components	N/A

<b>5</b>	<b>Electrical requirements and simulated abnormal conditions</b>		<b>P</b>
5.1	Touch current and protective conductor current		N/A
5.1.1	General	Class III equipment.	N/A
5.1.2	Configuration of equipment under test (EUT)		N/A
5.1.2.1	Single connection to an a.c. mains supply		N/A
5.1.2.2	Redundant multiple connections to an a.c. mains supply		N/A
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply		N/A
5.1.3	Test circuit		N/A
5.1.4	Application of measuring instrument		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.1.5	Test procedure		N/A
5.1.6	Test measurements		N/A
	Supply voltage (V) .....		—
	Measured touch current (mA) .....		—
	Max. allowed touch current (mA) .....		—
	Measured protective conductor current (mA) .....		—
	Max. allowed protective conductor current (mA).....		—
5.1.7	Equipment with touch current exceeding 3,5 mA		N/A
5.1.7.1	General .....		N/A
5.1.7.2	Simultaneous multiple connections to the supply		N/A
5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks		N/A
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system		N/A
	Supply voltage (V) .....		—
	Measured touch current (mA) .....		—
	Max. allowed touch current (mA) .....		—
5.1.8.2	Summation of touch currents from telecommunication networks		N/A
	a) EUT with earthed telecommunication ports .....		N/A
	b) EUT whose telecommunication ports have no reference to protective earth		N/A

<b>5.2</b>	<b>Electric strength</b>		<b>N/A</b>
5.2.1	General	Function insulation considered to 5.3.4 c)	N/A
5.2.2	Test procedure		N/A

<b>5.3</b>	<b>Abnormal operating and fault conditions</b>		<b>P</b>
5.3.1	Protection against overload and abnormal operation	(see appended table 5.3)	P
5.3.2	Motors	No such component	N/A
5.3.3	Transformers	No such component	N/A
5.3.4	Functional insulation.....	Complies with 5.3.4 c).	P
5.3.5	Electromechanical components	No such component	N/A
5.3.6	Audio amplifiers in ITE .....	No such component	N/A
5.3.7	Simulation of faults	(see appended table 5.3)	P

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.3.8	Unattended equipment		N/A
5.3.9	Compliance criteria for abnormal operating and fault conditions	(See appended table 5.3)	P
5.3.9.1	During the tests	No hazards	P
5.3.9.2	After the tests		N/A

<b>6</b>	<b>Connection to telecommunication networks</b>		<b>N/A</b>
6.1	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment		N/A
6.1.1	Protection from hazardous voltages		N/A
6.1.2	Separation of the telecommunication network from earth		N/A
6.1.2.1	Requirements	No TNV circuit.	N/A
	Supply voltage (V) .....		—
	Current in the test circuit (mA) .....		—
6.1.2.2	Exclusions .....		N/A

<b>6.2</b>	<b>Protection of equipment users from overvoltages on telecommunication networks</b>		<b>N/A</b>
6.2.1	Separation requirements		N/A
6.2.2	Electric strength test procedure		N/A
6.2.2.1	Impulse test		N/A
6.2.2.2	Steady-state test		N/A
6.2.2.3	Compliance criteria		N/A

<b>6.3</b>	<b>Protection of the telecommunication wiring system from overheating</b>		<b>N/A</b>
	Max. output current (A) .....		—
	Current limiting method .....		—

<b>7</b>	<b>Connection to cable distribution systems</b>		<b>N/A</b>
7.1	General	Not connected to Cable Distribution System.	N/A
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment		N/A
7.3	Protection of equipment users from overvoltages on the cable distribution system		N/A
7.4	Insulation between primary circuits and cable distribution systems		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
7.4.1	General		N/A
7.4.2	Voltage surge test		N/A
7.4.3	Impulse test		N/A

<b>Annex A</b>	<b>Tests for resistance to heat and fire</b>	<b>N/A</b>
A.1	Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2)	N/A
A.1.1	Samples.....:	—
	Wall thickness (mm).....:	—
A.1.2	Conditioning of samples; temperature (°C).....:	N/A
A.1.3	Mounting of samples.....:	N/A
A.1.4	Test flame (see IEC 60695-11-3)	N/A
	Flame A, B, C or D.....:	—
A.1.5	Test procedure	N/A
A.1.6	Compliance criteria	N/A
	Sample 1 burning time (s).....:	—
	Sample 2 burning time (s).....:	—
	Sample 3 burning time (s).....:	—
A.2	Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)	N/A
A.2.1	Samples, material.....:	—
	Wall thickness (mm).....:	—
A.2.2	Conditioning of samples; temperature (°C).....:	N/A
A.2.3	Mounting of samples.....:	N/A
A.2.4	Test flame (see IEC 60695-11-4)	N/A
	Flame A, B or C.....:	—
A.2.5	Test procedure	N/A
A.2.6	Compliance criteria	N/A
	Sample 1 burning time (s).....:	—
	Sample 2 burning time (s).....:	—
	Sample 3 burning time (s).....:	—
A.2.7	Alternative test acc. to IEC 60695-11-5, cl. 5 and 9	N/A
	Sample 1 burning time (s).....:	—
	Sample 2 burning time (s).....:	—
	Sample 3 burning time (s).....:	—
A.3	Hot flaming oil test (see 4.6.2)	N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
A.3.1	Mounting of samples		N/A
A.3.2	Test procedure		N/A
A.3.3	Compliance criterion		N/A

<b>Annex B</b>	<b>Motor tests under abnormal conditions (see 4.7.2.2 and 5.3.2)</b>	<b>N/A</b>
B.1	General requirements	N/A
	Position .....	—
	Manufacturer .....	—
	Type .....	—
	Rated values .....	—
B.2	Test conditions	N/A
B.3	Maximum temperatures	N/A
B.4	Running overload test	N/A
B.5	Locked-rotor overload test	N/A
	Test duration (days) .....	—
	Electric strength test: test voltage (V) .....	—
B.6	Running overload test for d.c. s in secondary circuits	N/A
B.6.1	General	N/A
B.6.2	Test procedure	N/A
B.6.3	Alternative test procedure	N/A
B.6.4	Electric strength test; test voltage (V) .....	N/A
B.7	Locked-rotor overload test for d.c. motors in secondary circuits	N/A
B.7.1	General	N/A
B.7.2	Test procedure	N/A
B.7.3	Alternative test procedure	N/A
B.7.4	Electric strength test; test voltage (V) .....	N/A
B.8	Test for motors with capacitors	N/A
B.9	Test for three-phase motors	N/A
B.10	Test for series motors	N/A
	Operating voltage (V) .....	—

<b>Annex C</b>	<b>Transformers (see 1.5.4 and 5.3.3)</b>	<b>N/A</b>
	Position .....	—
	Manufacturer .....	—
	Type .....	—

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Rated values .....		—
	Method of protection.....		—
C.1	Overload test		N/A
C.2	Insulation		N/A
	Protection from displacement of windings.....		N/A

<b>Annex D</b>	<b>Measuring instruments for touch-current testes(see 5.1.4)</b>	<b>N/A</b>
D.1	Measuring instrument	N/A
D.2	Alternative measuring instrument	N/A

<b>Annex E</b>	<b>Temperature rise of a winding (see 1.4.13)</b>	<b>N/A</b>
----------------	---	------------

<b>Annex F</b>	<b>Measurement of clearances and creepage distances (see 2.10 and Annex G)</b>	<b>N/A</b>
----------------	--	------------

<b>Annex G</b>	<b>Alternative method for determining minimum clearances</b>	<b>N/A</b>
G.1	Clearances	N/A
G.1.1	General	N/A
G.1.2	Summary of the procedure for determining minimum clearances	N/A
G.2	Determination of mains transient voltage (V)	N/A
G.2.1	AC mains supply .....	N/A
G.2.2	Earthed d.c. mains supplies .....	N/A
G.2.3	Unearthed d.c. mains supplies .....	N/A
G.2.4	Battery operation .....	N/A
G.3	Determination of telecommunication network transient voltage (V) .....	N/A
G.4	Determination of required withstand voltage (V)	N/A
G.4.1	Mains transients and internal repetitive peaks .....	N/A
G.4.2	Transients from telecommunication networks .....	N/A
G.4.3	Combination of transients	N/A
G.4.4	Transients from cable distribution systems	N/A
G.5	Measurement of transient voltages (V)	N/A
	a) Transients from a mains supply	N/A
	For an a.c. mains supply	N/A
	For a d.c. mains supply	N/A
	b) Transients from a telecommunication network	N/A
G.6	Determination of minimum clearances .....	N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

<b>Annex H</b>	<b>Ionizing radiation (see 4.3.13)</b>		<b>N/A</b>
----------------	--	--	------------

<b>Annex J</b>	<b>Table of electrochemical potentials (see 2.6.5.6)</b>		<b>N/A</b>
	Metal(s) used .....		—

<b>Annex K</b>	<b>Thermal controls (see 1.5.3 and 5.3.8)</b>		<b>N/A</b>
K.1	Making and breaking capacity		N/A
K.2	Thermostat reliability; operating voltage (V) .....		N/A
K.3	Thermostat endurance test; operating voltage (V) .....		N/A
K.4	Temperature limiter endurance; operating voltage (V) .....		N/A
K.5	Thermal cut-out reliability		N/A
K.6	Stability of operation		N/A

<b>Annex L</b>	<b>Normal load conditions for same types of electrical business equipment (see 1.2.2.1 and 4.5.2)</b>		<b>P</b>
L.1	Typewriters		N/A
L.2	Adding machines and cash registers		N/A
L.3	Erasers		N/A
L.4	Pencil sharpeners		N/A
L.5	Duplicators and copy machines		N/A
L.6	Motor-operated files		N/A
L.7	Other business equipment		P

<b>Annex M</b>	<b>Criteria for telephone ringing signals (see 2.3.1)</b>		<b>N/A</b>
M.1	Introduction		N/A
M.2	Method A		N/A
M.3	Method B		N/A
M.3.1	Ringing signal		N/A
M.3.1.1	Frequency (Hz) .....		—
M.3.1.2	Voltage (V) .....		—
M.3.1.3	Cadence; time (s), voltage (V) .....		—
M.3.1.4	Single fault current (mA) .....		—
M.3.2	Tripping device and monitoring voltage .....		N/A
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
M.3.2.2	Tripping device		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.3.2.3	Monitoring voltage (V) .....		N/A
<b>Annex N</b>	<b>Impulse test generators (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)</b>		<b>N/A</b>
N.1	ITU-T impulse test generators		N/A
N.2	IEC 60065 impulse test generator		N/A
<b>Annex P</b>	<b>Normative references</b>		—
<b>Annex Q</b>	<b>Voltage dependent resistors (VDRs) (see 1.5.9.1)</b>		<b>N/A</b>
	a) Preferred climatic categories .....		N/A
	b) Maximum continuous voltage .....		N/A
	c) Pulse current .....		N/A
	Body of the VDR Test according to IEC 60695-11-5 .....		N/A
	Body of the VDR. Flammability class of material (min. V-1) .....		N/A
<b>Annex R</b>	<b>Examples of requirements for quality control programmes</b>		<b>N/A</b>
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)		N/A
R.2	Reduced clearances (see 2.10.3)		N/A
<b>Annex S</b>	<b>Procedure for impulse testing (see 6.2.2.3)</b>		<b>N/A</b>
S.1	Test equipment		N/A
S.2	Test procedure		N/A
S.3	Examples of waveforms during impulse testing		N/A
<b>Annex T</b>	<b>Guidance on protection against ingress of water (see 1.1.2)</b>		<b>N/A</b>
			—
<b>Annex U</b>	<b>Insulated winding wires for use without interleaved insulation (see 2.10.5.4)</b>		<b>N/A</b>
			—
<b>Annex V</b>	<b>AC power distribution systems (see 1.6.1)</b>		<b>N/A</b>
V.1	Introduction		N/A
V.2	TN power distribution systems		N/A

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

<b>Annex W</b>	<b>Summation of touch currents</b>		<b>N/A</b>
W.1	Touch current from electronic circuits		N/A
W.1.1	Floating circuits		N/A
W.1.2	Earthed circuits		N/A
W.2	Interconnection of several equipments		N/A
W.2.1	Isolation		N/A
W.2.2	Common return, isolated from earth		N/A
W.2.3	Common return, connected to protective earth		N/A

<b>Annex X</b>	<b>Maximum heating effect in transformer tests (see clause C.1)</b>		<b>N/A</b>
X.1	Determination of maximum input current		N/A
X.2	Overload test procedure		N/A

<b>Annex Y</b>	<b>Ultraviolet light conditioning test (see 4.3.13.3)</b>		<b>N/A</b>
Y.1	Test apparatus .....		N/A
Y.2	Mounting of test samples .....		N/A
Y.3	Carbon-arc light-exposure apparatus .....		N/A
Y.4	Xenon-arc light exposure apparatus .....		N/A

<b>Annex Z</b>	<b>Overvoltage categories (see 2.10.3.2 and Clause G.2)</b>		<b>N/A</b>
----------------	---	--	------------

<b>Annex AA</b>	<b>Mandrel test (see 2.10.5.8)</b>		<b>N/A</b>
-----------------	------------------------------------	--	------------

<b>Annex BB</b>	<b>Changes in the second edition</b>		<b>—</b>
-----------------	--------------------------------------	--	----------

<b>Annex CC</b>	<b>Evaluation of integrated circuit (IC) current limiters</b>		<b>N/A</b>
CC.1	General		N/A
CC.2	Test program 1 .....		—
CC.3	Test program 2 .....		—

<b>Annex DD</b>	<b>Requirements for the mounting means of rack-mounted equipment</b>		<b>N/A</b>
DD.1	General		N/A
DD.2	Mechanical strength test, variable N .....		—
DD.3	Mechanical strength test, 250N, including end stops:		—
DD.4	Compliance.....		N/A

<b>Annex EE</b>	<b>Household and home/office document/media shredders</b>		<b>N/A</b>
-----------------	---	--	------------

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
EE.1	General		N/A
EE.2	Markings and instructions		N/A
	Use of markings or symbols .....		N/A
	Information of user instructions, maintenance and/or servicing instructions .....		N/A
EE.3	Inadvertent reactivation test .....		N/A
EE.4	Disconnection of power to hazardous moving parts .....		N/A
	Use of markings or symbols .....		N/A
EE.5	Protection against hazardous moving parts		N/A
	Test with test finger (Figure 2A) .....		—
	Test with wedge probe (Figure EE1 and EE2) .....		—

Group differences																																																																												
COMMON MODIFICATIONS for EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013																																																																												
Contents	Add the following annexes: Annex ZA (normative) Normative references to international publications with their corresponding European publications Annex ZB (normative) Special national conditions Annex ZC (informative) A-deviations			P																																																																								
Contents (A2:2013)	Add the following: Annex ZD (informative) IEC and CENELEC code designations for flexible cords			N/A																																																																								
Whole document (A2:2013)	Delete all the “country” notes in the reference document according to the following list: <table border="1" data-bbox="352 1375 1339 1420"> <tr> <td>2.7.1</td> <td>Note *</td> <td>2.10.3.1</td> <td>Note 2</td> <td>6.2.2</td> <td>Note</td> </tr> </table> * Note of secretary: Text of Common Modification remains unchanged For special national conditions, see Annex ZB.			2.7.1	Note *	2.10.3.1	Note 2	6.2.2	Note	N/A																																																																		
2.7.1	Note *	2.10.3.1	Note 2	6.2.2	Note																																																																							
General	Delete all the “country” notes in the reference document according to the following list: <table data-bbox="352 1579 1339 1944"> <tr> <td>1.4.8</td> <td>Note 2</td> <td>1.5.1</td> <td>Note 2 &amp; 3</td> <td>1.5.7.1</td> <td>Note</td> </tr> <tr> <td>1.5.8</td> <td>Note 2</td> <td>1.5.9.4</td> <td>Note</td> <td>1.7.2.1</td> <td>Note 4, 5 &amp; 6</td> </tr> <tr> <td>2.2.3</td> <td>Note</td> <td>2.2.4</td> <td>Note</td> <td>2.3.2</td> <td>Note</td> </tr> <tr> <td>2.3.2.1</td> <td>Note 2</td> <td>2.3.4</td> <td>Note 2</td> <td>2.6.3.3</td> <td>Note 2 &amp; 3</td> </tr> <tr> <td>2.7.1</td> <td>Note</td> <td>2.10.3.2</td> <td>Note 2</td> <td>2.10.5.13</td> <td>Note 3</td> </tr> <tr> <td>3.2.1.1</td> <td>Note</td> <td>3.2.4</td> <td>Note</td> <td>3.2.5.1</td> <td>Note 2</td> </tr> <tr> <td>4.3.6</td> <td>Note 1 &amp; 2</td> <td>4.7</td> <td>Note 4</td> <td>4.7.2.2</td> <td>Note</td> </tr> <tr> <td>4.7.3.1</td> <td>Note 2</td> <td>5.1.7.1</td> <td>Note 3 &amp; 4</td> <td>5.3.7</td> <td>Note 1</td> </tr> <tr> <td>6</td> <td>Note 2 &amp; 5</td> <td>6.1.2.1</td> <td>Note 2</td> <td>6.1.2.2</td> <td>Note</td> </tr> <tr> <td>6.2.2</td> <td>Note</td> <td>6.2.2.1</td> <td>Note 2</td> <td>6.2.2.2</td> <td>Note</td> </tr> <tr> <td>7.1</td> <td>Note 3</td> <td>7.2</td> <td>Note</td> <td>7.3</td> <td>Note 1 &amp; 2</td> </tr> <tr> <td>G.2.1</td> <td>Note 2</td> <td>Annex H</td> <td>Note 2</td> <td></td> <td></td> </tr> </table>			1.4.8	Note 2	1.5.1	Note 2 & 3	1.5.7.1	Note	1.5.8	Note 2	1.5.9.4	Note	1.7.2.1	Note 4, 5 & 6	2.2.3	Note	2.2.4	Note	2.3.2	Note	2.3.2.1	Note 2	2.3.4	Note 2	2.6.3.3	Note 2 & 3	2.7.1	Note	2.10.3.2	Note 2	2.10.5.13	Note 3	3.2.1.1	Note	3.2.4	Note	3.2.5.1	Note 2	4.3.6	Note 1 & 2	4.7	Note 4	4.7.2.2	Note	4.7.3.1	Note 2	5.1.7.1	Note 3 & 4	5.3.7	Note 1	6	Note 2 & 5	6.1.2.1	Note 2	6.1.2.2	Note	6.2.2	Note	6.2.2.1	Note 2	6.2.2.2	Note	7.1	Note 3	7.2	Note	7.3	Note 1 & 2	G.2.1	Note 2	Annex H	Note 2			P
1.4.8	Note 2	1.5.1	Note 2 & 3	1.5.7.1	Note																																																																							
1.5.8	Note 2	1.5.9.4	Note	1.7.2.1	Note 4, 5 & 6																																																																							
2.2.3	Note	2.2.4	Note	2.3.2	Note																																																																							
2.3.2.1	Note 2	2.3.4	Note 2	2.6.3.3	Note 2 & 3																																																																							
2.7.1	Note	2.10.3.2	Note 2	2.10.5.13	Note 3																																																																							
3.2.1.1	Note	3.2.4	Note	3.2.5.1	Note 2																																																																							
4.3.6	Note 1 & 2	4.7	Note 4	4.7.2.2	Note																																																																							
4.7.3.1	Note 2	5.1.7.1	Note 3 & 4	5.3.7	Note 1																																																																							
6	Note 2 & 5	6.1.2.1	Note 2	6.1.2.2	Note																																																																							
6.2.2	Note	6.2.2.1	Note 2	6.2.2.2	Note																																																																							
7.1	Note 3	7.2	Note	7.3	Note 1 & 2																																																																							
G.2.1	Note 2	Annex H	Note 2																																																																									

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
General (A1:2010)	In IEC 60950-1:2005/A1 delete all the "country" notes according to the following list: - 1.5.7.1: Note - 6.1.2.1: Note 2 - 6.2.2.1: Note 2 - EE.3: Note		N
1.1.1 (A1:2010)	Replace the text of NOTE 3 by the following NOTE 3 The requirements of EN 60065 may also be used to meet safety requirements for multimedia equipment. See IEC Guide 112, Guide on the safety of multimedia equipment. For television sets EN 60065 applies.		N
1.2.3 (A1:2010)	Add the following definition: <b>1.2.3.Z1</b> <b>PORTABLE SOUND SYSTEM</b> small battery powered audio equipment: - whose prime purpose is to listen to recorded or broadcasted sound; and - that uses headphones or earphones that can be worn in or on or around the ears; and - that allows the user to walk around NOTE Examples are mini-disk or CD players; MP3 audio players or similar equipment.		N
1.3.Z1	Add the following subclause: 1.3.Z1 Exposure to excessive sound pressure The apparatus shall be so designed and constructed as to present no danger when used for its intended purpose, either in normal operating conditions or under fault conditions, particularly providing protection against exposure to excessive sound pressures from headphones or earphones. NOTE Z1 A new method of measurement is described in EN 50332-1, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 1: General method for "one package equipment", and in EN 50332-2, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 2: Guidelines to associate sets with headphones coming from different manufacturers.		N
1.5.1	Add the following NOTE: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.2.1	Add the following NOTE: NOTE Z1 In addition, the instructions shall include, as far as applicable, a warning that excessive sound pressure from earphones and headphones can cause hearing loss		N
1.7.2.1 (A1:2010)	Delete NOTE Z1. Add the following paragraph at the end of the subclause: In addition, for a PORTABLE SOUND SYSTEM, the instructions shall include a warning that excessive sound pressure from earphones and headphones can cause hearing loss.		N
2.7.1	Replace the subclause as follows: Basic requirements To protect against excessive current, short-circuits and earth faults in PRIMARY CIRCUITS, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c): a) except as detailed in b) and c), protective devices necessary to comply with the requirements of 5.3 shall be included as parts of the equipment; b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation; c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions.  If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.		N
2.7.2	This subclause has been declared 'void'.		N
3.2.3	Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.		N

IEC/EN 60950-1															
Clause	Requirement + Test	Result - Remark	Verdict												
3.2.5.1	<p>Replace            “60245 IEC 53” by “H05 RR-F”;            “60227 IEC 52” by “H03 VV-F or H03 VVH2-F”;            “60227 IEC 53” by “H05 VV-F or H05 VVH2-F2”.</p> <p>In Table 3B, replace the first four lines by the following:</p> <table border="0"> <tr> <td>  Up to and including 6</td> <td> </td> </tr> <tr> <td>0,75 <sup>a)</sup>  </td> <td></td> </tr> <tr> <td>  Over 6 up to and including 10</td> <td>  (0,75) <sup>b)</sup></td> </tr> <tr> <td>1,0  </td> <td></td> </tr> <tr> <td>  Over 10 up to and including 16</td> <td>  (1,0) <sup>c)</sup> 1,5</td> </tr> <tr> <td> </td> <td></td> </tr> </table> <p>In the conditions applicable to Table 3B delete the words “in some countries” in condition <sup>a)</sup>.</p> <p>In NOTE 1, applicable to Table 3B, delete the second sentence.</p>	Up to and including 6		0,75 <sup>a)</sup>		Over 6 up to and including 10	(0,75) <sup>b)</sup>	1,0		Over 10 up to and including 16	(1,0) <sup>c)</sup> 1,5				N
Up to and including 6															
0,75 <sup>a)</sup>															
Over 6 up to and including 10	(0,75) <sup>b)</sup>														
1,0															
Over 10 up to and including 16	(1,0) <sup>c)</sup> 1,5														
3.2.5.1 (A2:2013)	<p>Add the following Note:            NOTE Z1 The harmonised code designations corresponding to the IEC cord types are given in Annex ZD.</p>		N												
3.3.4	<p>In Table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following:</p> <table border="0"> <tr> <td>  Over 10 up to and including 16</td> <td>  1,5 to 2,5  </td> </tr> <tr> <td>1,5 to 4  </td> <td></td> </tr> </table> <p>Delete the fifth line: conductor sizes for 13 to 16 A.</p>	Over 10 up to and including 16	1,5 to 2,5	1,5 to 4			N								
Over 10 up to and including 16	1,5 to 2,5														
1,5 to 4															
4.3.13.6	<p>Add the following NOTE:            NOTE Z1 Attention is drawn to 1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz. Standards taking into account this Recommendation which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.</p>		N												
4.3.13.6 (A1:2010)	<p>Replace the existing NOTE by the following:            NOTE Z1 Attention is drawn to :            1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz, and            2006/25/EC: Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artificial optical radiation).            Standards taking into account mentioned Recommendation and Directive which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.</p>		N												

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
Annex H	<p>Replace the last paragraph of this annex by: At any point 10 cm from the surface of the OPERATOR ACCESS AREA, the dose rate shall not exceed 1 <math>\mu</math>Sv/h (0,1 mR/h) (see NOTE). Account is taken of the background level. Replace the notes as follows: NOTE These values appear in Directive 96/29/Euratom. Delete NOTE 2.</p>		N
Bibliography	<p>Add the following standards: EN 50332-1:2000, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 1: General method for "one package equipment" EN 50332-2:2003, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations - Part 2: Matching of sets with headphones if either or both are offered separately Add the following notes for the standards indicated: IEC 60127 NOTE Harmonized in EN 60127 series (not modified). IEC 60369-2-1 NOTE Harmonized as HD 60369-2-1:2005 (modified). IEC 60364-4-41 NOTE Harmonized as HD 384.4.41 S2:1996 (modified). IEC 60529 NOTE Harmonized as EN 60529:1991 (not modified). IEC 60664-4 NOTE Harmonized as EN 60664-4:2006 (not modified). IEC 60728-11 NOTE Harmonized as EN 60728-11:2005 (modified). IEC 60896-21 NOTE Harmonized as EN 60896-21:2004 (not modified). IEC 60896-22 NOTE Harmonized as EN 60896-22:2004 (not modified). IEC 61032 NOTE Harmonized as EN 61032:1998 (not modified).</p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	<p>IEC 61140 NOTE Harmonized as EN 61140:2002 (not modified).</p> <p>IEC 61558-1 NOTE Harmonized as EN 61558-1:2005 (not modified).</p> <p>IEC 61643-21 NOTE Harmonized as EN 61643-21:2001 (not modified).</p> <p>IEC 61643-311 NOTE Harmonized as EN 61643-311:2001 (not modified).</p> <p>IEC 61643-321 NOTE Harmonized as EN 61643-321:2002 (not modified).</p> <p>IEC 61643-331 NOTE Harmonized as EN 61643-331:2003 (not modified).</p> <p>IEC 61965 NOTE Harmonized as EN 61965:2003 (not modified).</p> <p>ISO 4892 NOTE Harmonized in EN ISO 4892 series (not modified).</p>		N
Bibliography (A1:2010)	Add the following note for the standard indicated: IEC 60908 NOTE Harmonized as EN 60908.		N
<b>ZA</b> (A2:2013)	<b>Normative references to international publications with their corresponding European publications</b>		N
<b>ZB</b>	<b>Special national conditions</b> Special national condition: National characteristic or practice that cannot be changed even over a long period, e.g. climatic conditions, electrical earthing conditions. NOTE If it affects harmonization, it forms part of the European Standard. For the countries in which the relevant special national conditions apply these provisions are normative, for other countries they are informative.		N
1.2.4.1	In <b>Denmark</b> , certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.		N
1.2.13.14 (A11:2009)	Add as new SNC: In <b>Norway</b> and <b>Sweden</b> , for requirements see 1.7.2.1 and 7.3 of this annex.		N
1.5.7.1 (A11:2009)	Replace the existing SNC by the following: In <b>Finland, Norway</b> and <b>Sweden</b> , resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.		N
1.5.8	In <b>Norway</b> , due to the IT power system used (see annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.5.9.4	In <b>Finland, Norway and Sweden</b> , the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.		N
1.7.2.1 (A2:2013)	In <b>Denmark, Finland, Norway and Sweden</b> , CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in the applicable countries shall be as follows: In <b>Denmark</b> : "Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord." In <b>Finland</b> : "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan" In <b>Norway</b> : "Apparatet må tilkoples jordet stikkontakt" In <b>Sweden</b> : "Apparaten skall anslutas till jordat uttag"		N
1.7.5 (A2:2013)	In <b>Denmark</b> , socket-outlets for providing power to other equipment shall be in accordance with the DS 60884-2-D1:2011. For class I equipment the following Standard Sheets are applicable: DK 1-3a, DK 1-1c, DK 1-1d, DK 1-5a or DK 1-7a, with the exception for STATIONARY EQUIPMENT where the socket-outlets shall be in accordance with Standard Sheet DK 1-1b, DK 1-1c, DK 1-1d or DK 1-5a. Socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance with DS 60884-2-D1 standard sheet DKA 1-4a. Other current rating socket outlets shall be in compliance with by DS 60884-2-D1 Standard Sheet DKA 1-3a or DKA 1-3b. Justification the Heavy Current Regulations, 6c		N
2.2.4	In <b>Norway</b> , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N
2.3.2	In <b>Finland, Norway and Sweden</b> there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.		N
2.3.4	In <b>Norway</b> , for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N
2.6.3.3	In the <b>United Kingdom</b> , the current rating of the circuit shall be taken as 13 A, not 16 A.		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.7.1	In the <b>United Kingdom</b> , to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.		N
2.10.5.13	In <b>Finland, Norway and Sweden</b> , there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.		N
3.2.1.1	<p>In <b>Switzerland</b>, supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets:</p> <p>SEV 6532-2.1991      Plug Type 15 3P+N+PE      250/400 V, 10 A SEV 6533-2.1991      Plug Type 11 L+N      250 V, 10 A SEV 6534-2.1991      Plug Type 12 L+N+PE      250 V, 10 A</p> <p>In general, EN 60309 applies for plugs for currents exceeding 10 A. However, a 16 A plug and socket-outlet system is being introduced in Switzerland, the plugs of which are according to the following dimension sheets, published in February 1998:</p> <p>SEV 5932-2.1998      Plug Type 25 3L+N+PE      230/400 V, 16 A SEV 5933-2.1998      Plug Type 21 L+N      250 V, 16 A SEV 5934-2.1998      Plug Type 23 L+N+PE      250 V, 16 A</p>		N
3.2.1.1 (A2:2013)	<p>In <b>Denmark</b>, supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.</p> <p>If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2.</p> <p>Justification the Heavy Current Regulations, 6c</p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
3.2.1.1	<p>In <b>Spain</b>, supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994. Supply cords of single-phase equipment having a rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994.</p> <p>If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.</p>		N
3.2.1.1	<p>In the <b>United Kingdom</b>, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and plug, shall be fitted with a 'standard plug' in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc. (Safety) Regulations 1994, unless exempted by those regulations.</p> <p>NOTE 'Standard plug' is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.</p>		N
3.2.1.1	<p>In <b>Ireland</b>, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997.</p>		N
3.2.4	<p>In <b>Switzerland</b>, for requirements see 3.2.1.1 of this annex.</p>		N
3.2.5.1	<p>In the <b>United Kingdom</b>, a power supply cord with conductor of 1,25 mm<sup>2</sup> is allowed for equipment with a rated current over 10 A and up to and including 13 A.</p>		N
3.3.4	<p>In the <b>United Kingdom</b>, the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is:</p> <ul style="list-style-type: none"> <li>• 1,25 mm<sup>2</sup> to 1,5 mm<sup>2</sup> nominal cross-sectional area.</li> </ul>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.3.6	In the <b>United Kingdom</b> , the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.		N
4.3.6	In <b>Ireland</b> , DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.		N
5.1.7.1	In <b>Finland, Norway and Sweden</b> TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the following equipment: <ul style="list-style-type: none"> <li>• STATIONARY PLUGGABLE EQUIPMENT TYPE A that <ul style="list-style-type: none"> <li>○ is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and</li> <li>○ has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and</li> <li>○ is provided with instructions for the installation of that conductor by a SERVICE PERSON;</li> </ul> </li> <li>• STATIONARY PLUGGABLE EQUIPMENT TYPE B;</li> <li>• STATIONARY PERMANENTLY CONNECTED EQUIPMENT.</li> </ul>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
6.1.2.1 (A1:2010)	<p>In <b>Finland, Norway and Sweden</b>, add the following text between the first and second paragraph of the compliance clause:</p> <p>If this insulation is solid, including insulation forming part of a component, it shall at least consist of either</p> <ul style="list-style-type: none"> <li>- two layers of thin sheet material, each of which shall pass the electric strength test below, or</li> <li>- one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below.</li> </ul> <p>Alternatively for components, there is no distance through insulation requirement for the insulation consisting of an insulating compound completely filling the casing, so that CLEARANCES and CREEPAGE DISTANCES do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition</p> <ul style="list-style-type: none"> <li>- passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 2.10.10 shall be performed using 1,5 kV), and</li> <li>- is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.</li> </ul> <p>It is permitted to bridge this insulation with an optocoupler complying with 2.10.5.4 b).</p> <p>It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2.</p> <p>A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions:</p> <ul style="list-style-type: none"> <li>- the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1;</li> <li>- the additional testing shall be performed on all the test specimens as described in EN 60384-14;</li> <li>- the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.</li> </ul>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
6.1.2.2	In <b>Finland, Norway and Sweden</b> , the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE B and equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.		N
7.2	In <b>Finland, Norway and Sweden</b> , for requirements see 6.1.2.1 and 6.1.2.2 of this annex. The term TELECOMMUNICATION NETWORK in 6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.		N
7.3 (A11:2009)	Delete the existing SNC for Norway and Sweden (based on NOTE 1 of IEC 60950-1:2005 + corr. 1). Add as new SNC (based on future NOTE 3 of IEC 60950-1:200X): In <b>Norway and Sweden</b> , for requirements see 1.2.13.14 and 1.7.2.1 of this annex.		N
7.3	In <b>Norway</b> , for installation conditions see EN 60728-11:2005.		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
<b>ZC</b>	<p><b>A-deviations</b></p> <p>A-deviation: National deviation due to regulations, the alteration of which is for the time being outside the competence of the CENELEC national member.</p> <p>This European Standard falls under Directives RTTED (1999/5/EC) and LVD (2006/95/EC).</p> <p>NOTE (from CEN/CENELEC IR Part 2:2002 , 2.17) Where standards fall under EC Directives, it is the view of the Commission of the European Communities (OJ No C 59, 1982-03-09) that the effect of the decision of the Court of Justice in case 815/79 Cremonini/Vrankovich (European Court Reports 1980, p. 3583) is that compliance with A-deviations is no longer mandatory and that the free movement of products complying with such a standard should not be restricted except under the safeguard procedure provided for in the relevant Directive.</p> <p>A-deviations in an EFTA-country are valid instead of the relevant provisions of the European Standard in that country until they have been removed.</p>		N
1.5.1	<p><b>Switzerland</b> (Ordinance on environmentally hazardous substances SR 814.081, Annex 1.7, Mercury - Annex 1.7 of SR 814.81 applies for mercury.)</p> <p>Add the following:</p> <p>NOTE In <b>Switzerland</b>, switches containing mercury such as thermostats, relays and level controllers are not allowed.</p>		N
1.7.2.1	<p><b>Germany</b> (Gesetz über technische Arbeitsmittel und Verbraucherprodukte (Geräte- und Produktsicherheitsgesetz – GPSG) [Law on technical labour equipment and consumer products], of 6th January 2004, Section 2, Article 4, Clause (4), Item 2).</p> <p>If for the assurance of safety and health certain rules during use, amending or maintenance of a technical labour equipment or readymade consumer product are to be followed, a manual in German language has to be delivered when placing the product on the market.</p> <p>Of this requirement, rules for use even only by SERVICE PERSONS are not exempted.</p>		N
1.7.13	<p><b>Switzerland</b> (Ordinance on chemical hazardous risk reduction SR 814.81, Annex 2.15 Batteries)</p> <p>Annex 2.15 of SR 814.81 applies for batteries.</p>		N
(A12:2011)	<p><b>Zx. Protection against excessive sound pressure from personal music players</b></p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	<p><b>Zx.1 General</b></p> <p>This sub-clause specifies requirements for protection against excessive sound pressure from personal music players that are closely coupled to the ear. It also specifies requirements for earphones and headphones intended for use with personal music players.</p> <p>A personal music player is a portable equipment for personal use, that:</p> <ul style="list-style-type: none"> <li>- is designed to allow the user to listen to recorded or broadcast sound or video; and</li> <li>- primarily uses headphones or earphones that can be worn in or on or around the ears; and</li> <li>- allows the user to walk around while in use.</li> </ul> <p>NOTE 1 Examples are hand-held or body-worn portable CD players, MP3 audio players, mobile phones with MP3 type features, PDA's or similar equipment.</p> <p>A personal music player and earphones or headphones intended to be used with personal music players shall comply with the requirements of this sub-clause.</p> <p>The requirements in this sub-clause are valid for music or video mode only.</p> <p>The requirements do not apply:</p> <ul style="list-style-type: none"> <li>- while the personal music player is connected to an external amplifier; or</li> <li>- while the headphones or earphones are not used.</li> </ul> <p>NOTE 2 An external amplifier is an amplifier which is not part of the personal music player or the listening device, but which is intended to play the music as a standalone music player.</p> <p>The requirements do not apply to:</p> <ul style="list-style-type: none"> <li>- hearing aid equipment and professional equipment;</li> </ul> <p>NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.</p>		N
	<ul style="list-style-type: none"> <li>- analogue personal music players (personal music players without any kind of digital processing of the sound signal) that are brought to the market before the end of 2015</li> </ul> <p>NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies.</p> <p>For equipment which is clearly designed or intended for use by young children, the limits of EN 71-1 apply.</p>		N


IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	<p><b>Zx.2 Equipment requirements</b></p> <p>No safety provision is required for equipment that complies with the following:</p> <ul style="list-style-type: none"> <li>- equipment provided as a package (personal music player with its listening device), where the acoustic output <math>L_{Aeq,T}</math> is <math>\leq 85</math> dBA measured while playing the fixed "programme simulation noise" as described in EN 50332-1; and</li> <li>- a personal music player provided with an analogue electrical output socket for a listening device, where the electrical output is <math>\leq 27</math> mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" as described in EN 50332-1.</li> </ul> <p>NOTE 1 Wherever the term acoustic output is used in this clause, the 30 s A-weighted equivalent sound pressure level <math>L_{Aeq,T}</math> is meant. See also Zx.5 and Annex Zx.</p> <p>All other equipment shall:</p> <ul style="list-style-type: none"> <li>a) protect the user from unintentional acoustic outputs exceeding those mentioned above; and</li> <li>b) have a standard acoustic output level not exceeding those mentioned above, and automatically return to an output level not exceeding those mentioned above when the power is switched off; and</li> <li>c) provide a means to actively inform the user of the increased sound pressure when the equipment is operated with an acoustic output exceeding those mentioned above. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an acoustic output exceeding those mentioned above. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time; and</li> </ul> <p>NOTE 2 Examples of means include visual or audible signals. Action from the user is always required.</p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	<p>NOTE 3 The 20 h listening time is the accumulative listening time, independent how often and how long the personal music player has been switched off.</p> <p>d) have a warning as specified in Zx.3; and</p> <p>e) not exceed the following:</p> <p>1) equipment provided as a package (player with its listening device), the acoustic output shall be <math>\leq 100</math> dBA measured while playing the fixed "programme simulation noise" described in EN 50332-1; and</p> <p>2) a personal music player provided with an analogue electrical output socket for a listening device, the electrical output shall be <math>\leq 150</math> mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" described in EN 50332-1.</p> <p>For music where the average sound pressure (long term <math>L_{Aeq,T}</math>) measured over the duration of the song is lower than the average produced by the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. In this case T becomes the duration of the song.</p> <p>NOTE 4 Classical music typically has an average sound pressure (long term <math>L_{Aeq,T}</math>) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the song and compare it with the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA.</p> <p>For example, if the player is set with the programme simulation noise to 85 dBA, but the average music level of the song is only 65 dBA, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dBA.</p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	<p><b>Zx.3 Warning</b>            The warning shall be placed on the equipment, or on the packaging, or in the instruction manual and shall consist of the following:</p> <ul style="list-style-type: none"> <li>- the symbol of Figure 1 with a minimum height of 5 mm; and</li> <li>- the following wording, or similar:              “To prevent possible hearing damage, do not listen at high volume levels for long periods.”</li> </ul> <div style="text-align: center;">  </div> <p><b>Figure 1 – Warning label (IEC 60417-6044)</b></p> <p>Alternatively, the entire warning may be given through the equipment display during use, when the user is asked to acknowledge activation of the higher level.</p>		N
	<p><b>Zx.4 Requirements for listening devices (headphones and earphones)</b></p>		N
	<p><b>Zx.4.1 Wired listening devices with analogue input</b>            With 94 dBA sound pressure output <math>L_{Aeq,T}</math>, the input voltage of the fixed “programme simulation noise” described in EN 50332-2 shall be <math>\geq 75</math> mV.            This requirement is applicable in any mode where the headphones can operate (active or passive), including any available setting (for example built-in volume level control).            NOTE The values of 94 dBA - 75 mV correspond with 85dBA - 27 mV and 100 dBA - 150 mV.</p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	<p><b>Zx.4.2 Wired listening devices with digital input</b>            With any playing device playing the fixed "programme simulation noise" described in EN 50332-1 (and respecting the digital interface standards, where a digital interface standard exists that specifies the equivalent acoustic level), the acoustic output <math>L_{Aeq,T}</math> of the listening device shall be <math>\leq 100</math> dBA.            This requirement is applicable in any mode where the headphones can operate, including any available setting (for example built-in volume level control, additional sound feature like equalization, etc.).            NOTE An example of a wired listening device with digital input is a USB headphone.</p>		N
	<p><b>Zx.4.3 Wireless listening devices</b>            In wireless mode:            - with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and            - respecting the wireless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and            - with volume and sound settings in the listening device (for example built-in volume level control, additional sound feature like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the above-mentioned programme simulation noise,            the acoustic output <math>L_{Aeq,T}</math> of the listening device shall be <math>\leq 100</math> dBA.            NOTE An example of a wireless listening device is a Bluetooth headphone.</p>		N
	<p><b>Zx.5 Measurement methods</b>            Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable. Unless stated otherwise, the time interval T shall be 30 s.            NOTE Test method for wireless equipment provided without listening device should be defined.</p>		N

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

<p>Annex Zx (A12:2011)</p>	<p><b>Significance of <math>L_{Aeq,T}</math> in EN 50332-1 and additional information</b></p> <p><math>L_{Aeq,T}</math> is derived from the general formula for equivalent sound pressure:</p> $L_{eq} = 10 \log \left[ \frac{1}{t_2 - t_1} \int_{t_1}^{t_2} \frac{p_A^2}{p_0^2} dt \right]$ <p>This can be represented graphically as follows:</p>  <p>In EN 50332-1 the measurement time interval (<math>t_2 - t_1</math>) is 30 s.</p> <p>In practice, and for the purposes of listening to personal music player content, <math>L_{Aeq,T}</math> has a time interval T (<math>t_2 - t_1</math>) in the order of minutes / hours and not seconds.</p> <p>6.5 (Limitation value) of EN 50332-1:2000 acknowledges this fact and states that the 100 dB limit equates to a long time average of 90 dB <math>L_{Aeq,T}</math>. By using the IEC 60268-1 "programme simulation noise" test signal, this also takes the spectral content into account.</p> <p>The SCENHIR<sup>1</sup> report states that 80 dBA is considered safe for an exposure time of 40 h/week. Most persons do not listen to 40 h/week to their personal music player. In addition, not all music tracks are at the same level of the simulated noise signal. Whilst modern music tends to be at around the same level, most of the available music is at a lower average level. Therefore, the working group<sup>2</sup> considers a value of 85 dBA to be safe for an overwhelming majority of the users of personal music players.</p>		<p>N</p>
	<p><sup>1</sup> SCENIHR opinion of 23 Sept 2008: Potential health risks of exposure to noise from personal music players and mobile phones including a music playing function</p> <p><sup>2</sup> CENELEC TC108X/WG03</p>		<p>N</p>

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
<b>ZD</b>	<b>IEC and CENELEC code designations for flexible cords</b>		N
	Type of flexible cord	Code designations IEC            CENELEC	N
	<b>PVC insulated cords</b>		
	Flat twin tinsel cord	60227 IEC 41            H03VH-Y	
	Light polyvinyl chloride sheathed flexible cord	60227 IEC 52            H03VV-F H03VVH2-F	
	Ordinary polyvinyl chloride sheathed flexible cord	60227 IEC 53            H05VV-F H05VVH2-F	
	<b>Rubber insulated cords</b>		
	Braided cord	60245 IEC 51            H03RT-F	
	Ordinary tough rubber sheathed flexible cord	60245 IEC 53            H05RR-F	
	Ordinary polychloroprene sheathed flexible cord	60245 IEC 57            H05RN-F	
	Heavy polychloroprene sheathed flexible cord	60245 IEC 66            H07RN-F	
	<b>Cords having high flexibility</b>		
	Rubber insulated and sheathed cord	60245 IEC 86            H03RR-H	
	Rubber insulated, crosslinked PVC sheathed cord	60245 IEC 87            H03RV4-H	
	Crosslinked PVC insulated and sheathed cord	60245 IEC 88            H03V4V4-H	

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.5.1	TABLE: List of critical components					P
Object/part No.	Manufacturer/ trademark	Type/ model	Technical data	Standard (Edition / year)	Mark(s) of conformity <sup>1)</sup>	
SWITCHING ADAPTER	SHENZHEN HEWEISHUN NETWORK TECHNOLOGY CO., LTD	BN036-A12012E, BN036-A12012B	Input: 100-240V~, 0.4A, 50/60Hz; Output: DC12V, 1.0A, LPS	IEC/EN 60950-1	CB Cert. No.: DK-46529-UL; CB TRF. No.: BTL-CB-1-S1504C201	
Enclosure	CHI MEI CORPORATION	PA-757(+), PA-757K(+)	HB, 80°C	UL 94	UL E56070	
(Alt.)	--	--	HB or better, Min. 80°C	UL 94	UL	
PCB	MEIZHOU BENCHUANG ELECTRONIC CO LTD	BC-2	V-0, 130°C	UL 796	UL E466435	
(Alt.)	--	--	V-1 or better, Min. 105°C	UL 796	UL	

<sup>1)</sup> An asterisk indicates a mark which assures the agreed level of surveillance.

1.5.1	TABLE: Opto Electronic Devices	N/A
Manufacturer.....: --		
Type.....: --		
Separately tested.....: --		
Bridging insulation.....: --		
External creepage distance.....: --		
Internal creepage distance.....: --		
Distance through insulation.....: --		
Tested under the following conditions.....: --		
Input.....: --		
Output.....: --		
Supplementary information:		

1.6.2	TABLE: Electrical data (in normal conditions)						P
U (V)	I (A)	Irated (A)	P (W)	Fuse #	Ifuse (A)	Condition/status	
90V50Hz	0.073	--	3.23	--	--	Normal operating.	
90V60Hz	0.074	--	3.23	--	--	Ditto	
100V50Hz	0.069	0.4	3.24	--	--	Ditto	
100V60Hz	0.069	0.4	3.22	--	--	Ditto	

IEC/EN 60950-1							
Clause	Requirement + Test					Result - Remark	Verdict
240V50Hz	0.041	0.4	3.29	--	--	Ditto	
240V60Hz	0.040	0.4	3.18	--	--	Ditto	
264V50Hz	0.040	--	3.21	--	--	Ditto	
264V60Hz	0.039	--	3.27	--	--	Ditto	
12.0VDC	0.265	--	--	--	--	Ditto	
Supplementary information: --							

2.1.1.5 c) 1)	TABLE: max. V, A, VA test					P
Voltage (rated) (V)	Current (rated) (A)	Voltage (max.) (V)	Current (max.) (A)	VA (max.) (VA)		
--	--	--	--	--		
Supplementary information: see appended table 2.5.						

2.1.1.5 c) 2)	TABLE: stored energy			N/A
Capacitance C (µF)	Voltage U (V)	Energy E (J)		
--	--	--		
Supplementary information:				

2.2	TABLE: evaluation of voltage limiting components in SELV circuits			N/A
Component (measured between)	Max. voltage (V) (normal operation)		Voltage Limiting Components	
	V peak	V d.c.		
--	--	--	--	
Fault test performed on voltage limiting components	Voltage measured (V) in SELV circuits (V peak or V d.c.)			
--	--			
Supplementary information:				

2.4.2	TABLE: limited current circuit measurement				N/A
Location	Voltage (V)	Current (mA)	Freq. (KHz)	Limit (mA)	
--	--	--	--	--	
Supplementary information:					

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

<b>2.5</b>	<b>TABLE: limited power sources</b>				<b>P</b>
Circuit output tested: see below					
Measured Uoc (V) with all load circuits disconnected.....: see below					
Conditions:	Uoc (V)	Isc (A)		VA	
		Meas.	Limit	Meas.	Limit
For lan port1					
Normal operating	1.0	0.55	8	0.51	100
T2 pin 16-20 SC	0	0	8	0	100
C389 SC	1.0	0.55	8	0.51	100
R194 SC	1.0	0.55	8	0.51	100
Supplementary information:					
1. SC=Short circuited; worst case had been considered.					
2. The test results for other lan ports were the same as above.					

<b>2.10.2</b>	<b>Table: working voltage measurement</b>			<b>N/A</b>
Location	Peak voltage (V)	RMS voltage (V)	Comments	
--	--	--	--	
Supplementary information:				

<b>2.10.3 and 2.10.4</b>	<b>TABLE: Clearance and creepage distance measurements</b>					<b>N/A</b>
Clearance (cl) and creepage distance (cr) at/of/between:	U peak (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	Required cr (mm)	cr (mm)
--	--	--	--	--	--	--
Supplementary information:						

<b>2.10.5</b>	<b>TABLE: Distance through insulation measurements</b>					<b>N/A</b>
Distance through insulation (DTI) at/of:	U peak (V)	U rms (V)	Test voltage (V)	Required DTI (mm)	DTI (mm)	
--	--	--	--	--	--	
--	--	--	--	--	--	
Supplementary information:						

<b>4.3.8</b>	<b>TABLE: Batteries</b>	<b>N/A</b>
--------------	-------------------------	------------

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

The tests of 4.3.8 are applicable only when appropriate battery data is not available		--		N/A					
Is it possible to install the battery in a reverse polarity position?		--		N/A					
	Non-rechargeable batteries			Rechargeable batteries					
	Discharging		Un-intentional charging	Charging		Discharging		Reversed charging	
	Meas. Current (A)	Manuf. Specs. (A)		Meas. Current (A)	Manuf. Specs. (A)	Meas. Current (A)	Manuf. Specs. (A)	Meas. Current (A)	Manuf. Specs. (A)
Max. current during normal condition	--	--	--	--	--	--	--	--	--
Max. current during fault condition	--	--	--	--	--	--	--	--	--
Test results:		--		Verdict					
- Chemical leaks		--		N/A					
- Explosion of the battery		--		N/A					
- Emission of flame or expulsion of molten metal		--		N/A					
- Electric strength tests of equipment after completion of tests		--		N/A					
Supplementary information:									

<b>4.3.8</b>	<b>TABLE: Batteries</b>	<b>N/A</b>
Battery category .....: --		
Manufacturer.....: --		
Type / model.....: --		
Voltage.....: --		
Capacity.....: --		
Tested and Certified by (incl. Ref. No.) .....: --		
Circuit protection diagram: --		

<b>MARKINGS AND INSTRUCTIONS (1.7.13 )</b>	
Location of replaceable battery	No battery
Language(s).....: --	
Close to the battery.....: --	
In the servicing instructions .....: --	

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

In the operating instructions.....: --
--

<b>4.5</b>	<b>TABLE: Thermal requirements</b>				<b>P</b>	
	Supply voltage (V) .....	12VDC (label down)	12VDC (label vertical)		—	
	Ambient Tmin (°C) .....	24.0	Adjust to Tma=40	24.1	Adjust to Tma=40	—
	Ambient Tmax (°C) .....	24.4		24.3		—
Maximum measured temperature T of part/at:		T (°C)			Allowed Tmax (°C)	
Plastic enclosure top		30.6	46.2	31.3	47.0	95
Plastic enclosure bottom		28.7	44.3	29.8	45.5	95
C36 body		31.2	46.8	31.9	47.6	105
U13 body (referenced for PCB)		49.0	64.6	48.5	64.2	105
U2 body (referenced for PCB)		53.4	69.0	52.1	67.8	105

Supplementary information:

Temperature T of winding:	t <sub>1</sub> (°C)	R <sub>1</sub> (Ω)	t <sub>2</sub> (°C)	R <sub>2</sub> (Ω)	T (°C)	Allowed Tmax (°C)	Insulation class

Supplementary information:

<b>4.5.5</b>	<b>TABLE: Ball pressure test of thermoplastic parts</b>		<b>N/A</b>
	Allowed impression diameter (mm) .....	≤ 2 mm	—

Part	Test temperature (°C)	Impression diameter (mm)
--	--	--

Supplementary information:

<b>4.7</b>	<b>TABLE: Resistance to fire</b>				<b>P</b>
Part	Manufacturer of material	Type of material	Thickness (mm)	Flammability class	Evidence
--	--	--	--	--	--

Supplementary information: see table 1.5.1.

<b>5.1</b>	<b>TABLE: touch current measurement</b>			<b>N/A</b>
------------	---	--	--	------------

Measured between:	Measured (mA)	Limit (mA)	Comments/conditions
--	--	--	--

Supplementary information:

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

<b>5.2</b>	<b>TABLE: Electric strength tests, impulse tests and voltage surge tests</b>		<b>N/A</b>
	Test voltage applied between:	Voltage shape (AC, DC, impulse, surge)	Test voltage (V) Breakdown Yes / No
	--	--	--
Supplementary information:			

<b>5.3</b>	<b>TABLE: Fault condition tests</b>					<b>P</b>
	Ambient temperature (°C) .....		24.0-26.0		---	
	Power source for EUT: Manufacturer, model/type, output rating.....		See appended table 1.5.1		---	
Component No.	Fault	Supply voltage (V)	Test time	Fuse #	Fuse Current (A)	Observation
Openings	Blocked	12VDC	2 hours	--	--	EUT working normally, no hazards.
LAN port 1 output	SC	12VDC	15 mins	--	--	LAN port 1 shut down immediately, no hazards.
C1	SC	12VDC	15 mins	--	--	Unit shut down immediately, no damaged, no hazards.
R15	SC	12VDC	15 mins	--	--	Unit shut down immediately, no damaged, no hazards.
C38	SC	12VDC	15 mins	--	--	EUT working normally, no hazards.
U4 pin 5-3	SC	12VDC	15 mins	--	--	Unit shut down immediately, no damaged, no hazards.
Supplementary information: 1. SC=Short circuited.						

<b>C.2</b>	<b>TABLE: transformers</b>						<b>N</b>
Loc.	Tested insulation	Working voltage peak / V (2.10.2)	Working voltage rms / V (2.10.2)	Required electric strength (5.2)	Required clearance / mm (2.10.3)	Required creepage distance / mm (2.10.4)	Required distance thr. insul. (2.10.5)
--	--	--	--	--	--	--	--
Loc.	Tested insulation			Test voltage/ V	Measured clearance / mm	Measured creepage dist./ mm	Measured distance thr. insul. / mm; number of layers
--	--			--	--	--	--
supplementary information: --							

IEC/EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

<b>C.2</b>	<b>TABLE: transformers</b>		N

FINAL

**Appendix A EUT Photos**



Photo 1 overall view



Photo 2 EUT bottom view



Photo 3 terminals view




Photo 4 internal view




Photo 5 PCB top view




Photo 6 PCB bottom view



**Appendix B Test Equipment List**

Equipment Description	Model No.	Equipment No.	Manufacturer	Last Cal	Cal Due
AC power system	HPC3145	T-08-SF191	N/A	2017-03-31	2018-03-30
Hybrid Recorder	DR240	T-08-SF013	YOKOGAWA	2017-03-03	2018-03-02
Hygrothermograph	HTC-1	T-08-QA075	N/A	2016-12-06	2017-12-05
Power meter	760401	T-08-SF125	everfine	2017-01-03	2018-01-02
Digital Multimeter	15B	T-08-SF072	FLUKE	2017-03-03	2018-03-02
Electric load	3710A	T-08-SF077	ITEK POWER	2016-12-10	2017-12-10
Steel tape	HILOCK-19	T-08-SF100	TAJIMA	2013-04-18	2018-04-17
Digital Caliper	0-150mm	T-08-SF074	Guanglu	2017-03-03	2018-03-02
Stop Watch	PC396	T-08-SF086	N/A	2017-03-03	2018-03-02
Electron Balance	HZ-ALC-20C+	T-08-SF035	hengzhan	2017-03-03	2018-03-02
DC Power Supply	WY5015	T-08-EE127	everfine	2017-03-03	2018-03-02

\*\*\*End of Report\*\*\*