



中国认可
国际互认
检测
TESTING
CNAS L5662



EN 55032:2015+A11:2020+A1:2020*

EN 55035:2017+A11:2020

EN IEC 61000-3-2:2019+A1:2021

EN 61000-3-3:2013+A1:2019+A2:2021*

BS EN 55032:2015+A11:2020+A1:2020*

BS EN 55035:2017+A11:2020*

BS EN IEC 61000-3-2:2019+A1:2021*

BS EN 61000-3-3:2013+A1:2019+A2:2021*

TEST REPORT

For

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China. 518052

**Tested Model: Mesh12X
Multiple Models: MX12,EX12,EM12**


Report Type: Original Report	Product Type: AX3000 Whole Home Mesh Wi-Fi 6 System
Report Number: DG2220216-04699E-01	
Report Date: 2022-07-20	
Reviewed By: Rocky Xiao RF Engineer	
Approved By: Ivan Cao Assistant Manager	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Table of Contents

General Information.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE.....	4
TEST METHODOLOGY	4
DECLARATIONS	5
System Test Configuration	6
DESCRIPTION OF TEST CONFIGURATION.....	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
TEST EQUIPMENT LIST	7
ENVIRONMENTAL CONDITIONS.....	8
Summary of Test Results	9
1 – Conducted emissions	10
MEASUREMENT UNCERTAINTY.....	10
TEST SYSTEM SETUP	10
EMI TEST RECEIVER SETUP.....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST PROCEDURE.....	11
TEST DATA.....	12
2 – Radiated emissions.....	22
MEASUREMENT UNCERTAINTY.....	22
TEST SYSTEM SETUP	22
EMI TEST RECEIVER SETUP.....	23
TEST PROCEDURE.....	23
CORRECTED AMPLITUDE & MARGIN CALCULATION	23
TEST DATA.....	24
3 – Electrostatic discharges IEC 61000-4-2.....	32
MEASUREMENT UNCERTAINTY.....	32
TEST SYSTEM SETUP	32
TEST STANDARD	32
TEST PROCEDURE.....	33
TEST DATA.....	34
4 – Continuous radiated disturbances IEC 61000-4-3.....	36
MEASUREMENT UNCERTAINTY.....	36
TEST SYSTEM SETUP	36
TEST STANDARD	36
TEST LEVEL.....	37
TEST PROCEDURE.....	37
TEST DATA.....	37
5 – Continuous conducted disturbances IEC 61000-4-6.....	38
MEASUREMENT UNCERTAINTY.....	38
TEST SETUP	38
TEST STANDARD	38
TEST PROCEDURE.....	39
TEST DATA.....	39
6 – Power frequency magnetic fields IEC 61000-4-8.....	40
TEST SETUP	40
TEST STANDARD	40

TEST LEVEL.....	40
TEST PROCEDURE.....	40
TEST DATA.....	40
7 – Electrical fast transients/burst IEC 61000-4-4	41
MEASUREMENT UNCERTAINTY.....	41
TEST SYSTEM SETUP	41
TEST STANDARD	41
TEST PROCEDURE.....	42
TEST DATA	42
8 – Surges IEC 61000-4-5	43
TEST SYSTEM SETUP	43
TEST STANDARD	43
TEST PROCEDURE.....	43
TEST DATA	44
9 –Voltage dips and short interruptions IEC 61000-4-11	45
TEST SETUP	45
TEST STANDARD	45
TEST PROCEDURE.....	45
TEST DATA	46
10 – Harmonic current emissions.....	47
TEST SYSTEM SETUP	47
TEST STANDARD	47
TEST PRODUCT CLASS	47
TEST DATA	48
11 –Voltage fluctuations and flicker	49
TEST SYSTEM SETUP	49
TEST STANDARD	49
TEST DATA	50
ExhibitA – Eut Photographs.....	51
ExhibitB – Test Setup Photographs.....	52
CONDUCTED EMISSIONS_AC	52
CONDUCTED EMISSIONS_ISN.....	53
RADIATED EMISSIONS	54
ESD	56
RS.....	57
EFT	58
DIPS.....	59
CS.....	60
FLICKER.....	61
SURGE	62
DECLARATION OF SIMILARITY LETTER	63

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	AX3000 Whole Home Mesh Wi-Fi 6 System
EUT Model:	Mesh12X
Multiple Models:	MX12,EX12,EM12
Model Difference:	Refer to Dos
Rated Input Voltage:	12Vdc from adapter
Adapter Information	Model: BN067-A18012E
	Input: 100-240Vac 50/60Hz 0.6A
	Output: 12Vdc 1.5A
Serial Number:	DG2220216-04699E-RF-S1
EUT Received Date:	2022.02.18
EUT Received Status:	Good

Objective

This report is prepared on behalf of **SHENZHEN TENDA TECHNOLOGY CO.,LTD.** in accordance with EN 55032:2015+A11:2020+A1:2020* and BS EN 55032:2015+A11:2020+A1:2020* Electromagnetic compatibility of multimedia equipment — Emission Requirements; EN 55035:2017+A11:2020 and BS EN 55035:2017+A11:2020v

Electromagnetic compatibility of multimedia equipment — Immunity Requirements; EN IEC 61000-3-2:2019+A1:2021 and BS EN IEC 61000-3-2:2019+A1:2021* Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤ 16 A per phase); EN 61000-3-3:2013+A1:2019+A2:2021* and BS EN 61000-3-3:2013+A1:2019+A2:2021* Electromagnetic compatibility (EMC)Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection.

The objective is to determine the compliance of EUT with:
 EN 55032:2015+A11:2020+A1:2020*
 EN 55035:2017+A11:2020
 EN IEC 61000-3-2:2019+A1:2021
 EN 61000-3-3:2013+A1:2019+A2:2021*.
 BS EN 55032:2015+A11:2020+A1:2020*
 BS EN 55035:2017+A11:2020*
 BS EN IEC 61000-3-2:2019+A1:2021*
 BS EN 61000-3-3:2013+A1:2019+A2:2021*

Test Methodology

All measurements contained in this report were conducted with EN 55032:2015+A11:2020+A1:2020* and BS EN 55032:2015+A11:2020+A1:2020* Electromagnetic compatibility of multimedia equipment — Emission Requirements; EN 55035:2017+A11:2020 and BS EN 55035:2017+A11:2020* Electromagnetic compatibility of multimedia equipment — Immunity Requirements; EN IEC 61000-3-2:2019+A1:2021 and BS EN IEC 61000-3-2:2019+A1:2021* Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase); EN 61000-3-3:2013+A1:2019+A2:2021* and BS EN 61000-3-3:2013+A1:2019+A2:2021* Electromagnetic compatibility (EMC)Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Test Mode: Operating

Equipment Modifications

No modification was made to the EUT.

EUT Exercise Software

Software "Lantest.exe" and "Ping.exe" were used during test.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	E6410	GYXJ3 A00 JSD2
Huawei	Phone	BLN-AL40	BLN-AL40C00B120
Bacl	RJ45 Load	RJ45X8	F-EM-PHRJ45X8002

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length(m)	From Port	To
Power Cable	No	No	1.5	EUT	Adapter
RJ45 Cable	Yes	No	10	EUT	Laptop/RJ45 Load

Block Diagram of Test Setup



Test Equipment List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission					
R&S	LISN	ENV 216	101614	2021-09-11	2022-09-10
TESEQ	ISN	T800	34379	2021-09-11	2022-09-10
R&S	EMI Test Receiver	ESCI	101121	2021-07-22	2022-07-21
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2021-09-05	2022-09-04
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A
Radiated emissions below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-1	2020-11-10	2023-11-10
R&S	EMI Test Receiver	ESR3	102453	2021-09-22	2022-09-21
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2021-07-19	2022-07-18
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2021-07-19	2022-07-18
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2021-07-19	2022-07-18
Sonoma	Amplifier	310N	372193	2021-07-18	2022-07-17
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiated emissions above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2021-10-12	2024-10-11
Agilent	Spectrum Analyzer	E4440A	SG43360054	2021-07-22	2022-07-21
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2021-09-04	2022-09-03
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2021-09-04	2022-09-03
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sinoscite	Bandstop Filters	BSF5150-5850M N-0899-003	0899003	2021-05-06	2022-05-05
E-Microwave	Band-stop Filters	OBSF-2400-248 3.5-S	OE01601525	2021-06-16	2022-06-15
ESD					
HAEFELY	Electrostatic Discharge Simulator	ONYX	180786	2021-10-27	2022-10-26
EFT & Surge & Dips					
EM TEST	Ultra Compact Generator	UCS 500N5	P1406130994	2021-07-22	2022-07-21
EM TEST	Autotransformer	MV2616	P1450144859	N/A	N/A
EM TEST	CDN	CNV508 S1	311137	2022-01-26	2023-01-25
EM TEST	EFT Clamp	N/A	300886	2021-07-22	2022-07-21
Flicker & Harmonic					
ELGAR	AC Power Source	1751SX	5611	2022-01-05	2023-01-05
EM TEST	Harmonic & Flicker Analyzer	DPA 500	303278	2021-10-27	2022-10-26
CS					
HP	Signal Generator	8648A	3246A00831	2021-09-11	2022-09-10
R&S	Power Amplifier	15A250	12934	N/A	N/A
Werlatone	Dual Directional Coupler	C5091-10	113192	2022-02-09	2023-02-08
HP	Power Meter	HP EPM-441A	GB37481494	2021-07-22	2022-07-21
Agilent	8482A Power sensor	8482A	US37296108	2021-07-22	2022-07-21
NARDA	Attenuator	769-6	2754	N/A	N/A
COM-POWER	CDN	M325E	521064	2021-07-22	2022-07-21

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
COM-POWER	CDN	T8E	581607	2021-07-22	2022-07-21
RS					
AR	Antenna	ATL80M1G	0351400	N/A	N/A
AR	Antenna	ATT700M12G	0349410	N/A	N/A
HP	Signal Generator	8665B	3438a00584	2021-07-22	2022-07-21
AR	Power Amplifier	500W1000C	0353561	N/A	N/A
AR	Power Amplifier	60S1G6	0348711	N/A	N/A
PASTERNAK	Dual Directional Coupler	PE2239-30	1711	2021-07-15	2022-07-14
Agilent	EPM Series Power Meter	E4419B	MY45103907	2021-07-22	2022-07-21
Agilent	E-Series Avg Power Sensor	E9301A	MY41497625	2021-07-22	2022-07-21
Agilent	E-Series Avg Power Sensor	E9301A	MY41497628	2021-07-22	2022-07-21

Environmental Conditions

Test Item:	Conducted emission	Radiated emissions below 1GHz	Radiated emissions above 1GHz	EMS & Flicker*
Temperature:	22.3 °C	15.4°C	15.7°C	21.4~24.8°C
Relative Humidity:	66%	53%	58%	53~66 %
ATM Pressure:	100.9kPa	101.8kPa	102.2kPa	101.2 kPa
Tester:	Walker Chen	Leo Yuan	Bill Yang	April Wu
Test Date:	2022-03-07	2022-02-22	2022-02-24	2022-03-29

*Note: The **Relative Humidity** in ESD test site is 53%.

SUMMARY OF TEST RESULTS

SN	Rule and Clause	Description of Test	Test Result
1	EN 55032 Clause A.3	Conducted emissions	Compliant
2	EN 55032 Clause A.2	Radiated emissions	Compliant
3	EN 55035 Clause 4.2.1	Electrostatic discharges IEC 61000-4-2	Compliant
4	EN 55035 Clause 4.2.2.2	Continuous radiated disturbances IEC 61000-4-3	Compliant
5	EN 55035 Clause 4.2.2.3	Continuous conducted disturbances IEC 61000-4-6	Compliant
6	EN 55035 Clause 4.2.3	Power frequency magnetic fields IEC 61000-4-8	Not applicable
7	EN 55035 Clause 4.2.4	Electrical fast transients/burst IEC 61000-4-4	Compliant
8	EN 55035 Clause 4.2.5	Surges IEC 61000-4-5	Compliant
9	EN 55035 Clause 4.2.6	Voltage dips and short interruptions IEC 61000-4-11	Compliant
10	EN 61000-3-2	Harmonic current emissions	Not applicable
11	EN 61000-3-3	Voltage fluctuations and flicker	Compliant

1 – CONDUCTED EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to $U_{\text{cisp}}^{\text{pr}}$ of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than $U_{\text{cisp}}^{\text{pr}}$ of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}}^{\text{pr}})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}}^{\text{pr}})$, exceeds the disturbance limit.


Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz), and conducted disturbance at telecommunication port using AAN is 5.0 dB (150 kHz to 30 MHz).

Table 1 – Values of $U_{\text{cisp}}^{\text{pr}}$

Measurement	$U_{\text{cisp}}^{\text{pr}}$
Conducted disturbance at mains port using AMN (9 kHz to 150 kHz) (150 kHz to 30 MHz)	3.8 dB 3.4 dB
Conducted disturbance at mains port using voltage probe (9 kHz to 30 MHz)	2.9 dB
Conducted disturbance at telecommunication port using AAN (150 kHz to 30 MHz)	5.0 dB
Conducted disturbance at telecommunication port using CVP (150 kHz to 30 MHz)	3.9 dB
Conducted disturbance at telecommunication port using CP (150 kHz to 30 MHz)	2.9 dB

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test System Setup



- Note:
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with CISPR 16-1-1:2010+A1:2010+A2 2014, CISPR 16-2-1:2008+A1:2010+A2 2013 measurement procedure. The specification used was the EN 55032 Class B limits and BS EN 55032 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.

The adapter was connected to a 230V/50Hz AC line power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result (QuasiPeak or Average) = Meter Reading + Corr.

Note:

Corr. = Cable loss + Factor of coupling device

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit –Result

Test Procedure

During the conducted emissions test, the adapter of laptop was connected to the main outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination.


All data was recorded in the Quasi-peak and average detection mode.

Except for the recorded frequency points (no more than 6), the remaining frequency points have a margin more than 20dB.

Test Data

Please refer to following table and plots:

Port: L
 Test Mode: Operating
 Power Source: AC 110V/60Hz
 Note:




Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.202328	---	41.33	53.51	12.18	9.000	L1	9.6
0.206405	47.77	---	63.35	15.58	9.000	L1	9.6
0.303044	40.15	---	60.16	20.01	9.000	L1	9.6
0.309151	---	26.76	49.99	23.23	9.000	L1	9.6
0.621468	42.86	---	56.00	13.14	9.000	L1	9.6
0.621468	---	29.51	46.00	16.49	9.000	L1	9.6
0.736317	---	21.27	46.00	24.73	9.000	L1	9.7
0.809506	27.25	---	56.00	28.75	9.000	L1	9.7
17.478903	36.44	---	60.00	23.56	9.000	L1	10.1
17.654129	---	25.40	50.00	24.60	9.000	L1	10.1
26.975006	38.92	---	60.00	21.08	9.000	L1	10.1
27.245430	---	33.24	50.00	16.76	9.000	L1	10.1

Port:
Test Mode:
Power Source:
Note:


N
Operating
AC 110V/60Hz



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.204356	---	41.13	53.43	12.30	9.000	N	9.6
0.204356	45.24	---	63.43	18.19	9.000	N	9.6
0.295580	37.67	---	60.37	22.70	9.000	N	9.6
0.306082	---	26.75	50.08	23.33	9.000	N	9.6
0.615300	35.81	---	56.00	20.19	9.000	N	9.6
0.621468	---	30.18	46.00	15.82	9.000	N	9.6
0.781732	---	22.45	46.00	23.55	9.000	N	9.6
0.821710	25.03	---	56.00	30.97	9.000	N	9.6
16.218969	---	24.22	50.00	25.78	9.000	N	9.9
17.391943	32.34	---	60.00	27.66	9.000	N	9.9
27.656159	---	32.49	50.00	17.51	9.000	N	9.9
27.656159	38.79	---	60.00	21.21	9.000	N	9.9


Port: L
Test Mode: Operating
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.204356	---	34.11	53.43	19.32	9.000	L1	9.6
0.220231	43.78	---	62.81	19.03	9.000	L1	9.6
0.396710	43.77	---	57.92	14.15	9.000	L1	9.6
0.398694	---	29.63	47.88	18.25	9.000	L1	9.6
0.600145	41.32	---	56.00	14.68	9.000	L1	9.6
0.621468	---	29.39	46.00	16.61	9.000	L1	9.6
0.801471	28.77	---	56.00	27.23	9.000	L1	9.7
0.805479	---	22.11	46.00	23.89	9.000	L1	9.7
17.048409	35.72	---	60.00	24.28	9.000	L1	10.1
17.391943	---	25.35	50.00	24.65	9.000	L1	10.1
26.975006	---	33.21	50.00	16.79	9.000	L1	10.1
28.925869	37.86	---	60.00	22.14	9.000	L1	10.1


Port: N
Test Mode: Operating
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.202328	---	43.59	53.51	9.92	9.000	N	9.6
0.202328	50.58	---	63.51	12.93	9.000	N	9.6
0.309151	---	31.17	49.99	18.82	9.000	N	9.6
0.309151	45.30	---	59.99	14.69	9.000	N	9.6
0.612239	40.00	---	56.00	16.00	9.000	N	9.6
0.615300	---	31.15	46.00	14.85	9.000	N	9.6
0.736317	---	23.97	46.00	22.03	9.000	N	9.6
1.224625	32.54	---	56.00	23.46	9.000	N	9.6
1.332988	32.12	---	56.00	23.88	9.000	N	9.6
17.566298	---	29.42	50.00	20.58	9.000	N	9.9
18.281370	38.05	---	60.00	21.95	9.000	N	9.9
27.656159	---	31.71	50.00	18.29	9.000	N	9.9


Port: LAN
Test Mode: 10Mbps
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line
0.205378	---	60.22	71.39	11.17	9.000	Line 1
0.205378	65.31	---	81.39	16.08	9.000	Line 1
0.621468	---	50.20	64.00	13.80	9.000	Line 1
0.729009	54.21	---	74.00	19.79	9.000	Line 1
0.949586	48.06	---	74.00	25.94	9.000	Line 1
1.108363	---	42.93	64.00	21.07	9.000	Line 1
4.998419	52.04	---	74.00	21.96	9.000	Line 1
5.073771	---	42.64	64.00	21.36	9.000	Line 1
9.998049	67.45	---	74.00	6.55	9.000	Line 1
9.998049	---	53.00	64.00	11.00	9.000	Line 1
18.099918	---	48.22	64.00	15.78	9.000	Line 1
20.606025	51.08	---	74.00	22.92	9.000	Line 1


Port: LAN
Test Mode: 100Mbps
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.203339	---	60.96	71.47	10.51	9.000	Line 1	10.0
0.205378	65.44	---	81.39	15.95	9.000	Line 1	10.0
0.621468	---	50.33	64.00	13.67	9.000	Line 1	9.8
0.621468	56.80	---	74.00	17.20	9.000	Line 1	9.8
0.963901	49.48	---	74.00	24.52	9.000	Line 1	9.7
1.113905	---	43.38	64.00	20.62	9.000	Line 1	9.7
2.228079	46.34	---	74.00	27.66	9.000	Line 1	9.6
3.953919	---	43.42	64.00	20.58	9.000	Line 1	9.6
7.375399	---	47.55	64.00	16.45	9.000	Line 1	9.6
10.882741	51.80	---	74.00	22.20	9.000	Line 1	9.6
19.899024	52.31	---	74.00	21.69	9.000	Line 1	9.7
21.659819	---	54.83	64.00	9.17	9.000	Line 1	9.7


Port: LAN
Test Mode: 1000Mbps
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.205378	---	59.95	71.39	11.44	9.000	Line 1	10.0
0.208474	64.28	---	81.27	16.99	9.000	Line 1	10.0
0.600145	57.08	---	74.00	16.92	9.000	Line 1	9.8
0.618376	---	51.11	64.00	12.89	9.000	Line 1	9.8
1.113905	---	43.27	64.00	20.73	9.000	Line 1	9.7
1.142032	52.28	---	74.00	21.72	9.000	Line 1	9.7
2.151633	47.52	---	74.00	26.48	9.000	Line 1	9.6
4.434526	---	42.73	64.00	21.27	9.000	Line 1	9.6
10.561897	52.07	---	74.00	21.93	9.000	Line 1	9.6
11.728143	---	45.82	64.00	18.18	9.000	Line 1	9.6
17.654129	---	46.21	64.00	17.79	9.000	Line 1	9.6
19.408925	50.52	---	74.00	23.48	9.000	Line 1	9.7


Port: WAN
Test Mode: 10Mbps
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.204356	---	60.48	71.43	10.95	9.000	Line 1	10.0
0.205378	65.08	---	81.39	16.31	9.000	Line 1	10.0
0.615300	57.29	---	74.00	16.71	9.000	Line 1	9.8
0.621468	---	50.24	64.00	13.76	9.000	Line 1	9.8
1.113905	---	43.68	64.00	20.32	9.000	Line 1	9.7
1.136351	51.52	---	74.00	22.48	9.000	Line 1	9.7
5.048528	51.66	---	74.00	22.34	9.000	Line 1	9.6
5.073771	---	43.62	64.00	20.38	9.000	Line 1	9.6
9.998049	70.20	---	74.00	3.80	9.000	Line 1	9.6
9.998049	---	55.49	64.00	8.51	9.000	Line 1	9.6
18.190418	---	49.48	64.00	14.52	9.000	Line 1	9.7
18.930896	54.70	---	74.00	19.30	9.000	Line 1	9.7


Port: WAN
 Test Mode: 100Mbps
 Power Source: AC 230V/50Hz
 Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.201321	---	60.85	71.56	10.71	9.000	Line 1	10.0
0.201321	65.43	---	81.56	16.13	9.000	Line 1	10.0
0.612239	56.58	---	74.00	17.42	9.000	Line 1	9.8
0.618376	---	51.22	64.00	12.78	9.000	Line 1	9.8
1.142032	52.45	---	74.00	21.55	9.000	Line 1	9.7
1.268136	---	43.71	64.00	20.29	9.000	Line 1	9.7
3.005345	48.30	---	74.00	25.70	9.000	Line 1	9.6
4.412464	---	44.72	64.00	19.28	9.000	Line 1	9.6
7.375399	---	48.47	64.00	15.53	9.000	Line 1	9.6
12.389561	52.87	---	74.00	21.13	9.000	Line 1	9.6
13.418776	---	51.69	64.00	12.31	9.000	Line 1	9.6
19.120678	54.10	---	74.00	19.90	9.000	Line 1	9.7

Port: WAN
Test Mode: 1000Mbps
Power Source: AC 230V/50Hz
Note:



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.196363	64.38	---	81.76	17.38	9.000	Line 1	10.1
0.202328	---	61.10	71.51	10.41	9.000	Line 1	10.0
0.603146	56.71	---	74.00	17.29	9.000	Line 1	9.8
0.618376	---	50.29	64.00	13.71	9.000	Line 1	9.8
1.125072	---	43.60	64.00	20.40	9.000	Line 1	9.7
1.966886	49.15	---	74.00	24.85	9.000	Line 1	9.6
4.924186	48.44	---	74.00	25.56	9.000	Line 1	9.6
4.924186	---	41.65	64.00	22.35	9.000	Line 1	9.6
11.382374	---	46.98	64.00	17.02	9.000	Line 1	9.6
11.439286	52.47	---	74.00	21.53	9.000	Line 1	9.6
18.099918	55.63	---	74.00	18.37	9.000	Line 1	9.6
18.190418	---	49.47	64.00	14.53	9.000	Line 1	9.7

2 – RADIATED EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp}_r of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp}_r of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}}_r)$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}}_r)$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 10m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.55 dB for Horizontal, 4.57 dB for Vertical; 200M~1GHz: 4.66 dB for Horizontal, 4.56 dB for Vertical; measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB.


Table 1 – Values of U_{cisp}_r

Measurement	U_{cisp}_r
Radiated disturbance(electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB


Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test System Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests below 1GHz were performed in 3meters,above 1GHz were performed in the 3 meters, using the setup accordance with the CISPR 16-1-1:2010+A1:2010, CISPR 16-1-4:2010, CISPR 16-2-3:2010. The specification used was EN 55032 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle.

The spacing between the peripherals was 10cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 6GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	Peak
	1MHz	10Hz	/	Ave.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

During the radiated emissions, maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Meter Reading + Corrected

Note:

Corrected = Antenna Factor + Cable Loss - Amplifier Gain

or

Corrected = Antenna Factor + Cable Loss + Insertion loss of attenuator - Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit.

For example, a margin of 7dB means the emission is 7dB below the limit for Class B. The equation for margin calculation is as follows:

Margin = Limit - Result


Test Data

Please refer to following table and plots:

Below 1G

Condition: EN 55032 Class B 3m Radiation
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating


Polarization: Horizontal
Power: AC 110V/60Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.0000	31.27	peak	-3.49	27.78	40.00	12.22
2	110.5100	38.72	peak	-11.92	26.80	40.00	13.20
3	119.2400	37.64	peak	-10.65	26.99	40.00	13.01
4	135.7300	38.24	peak	-11.24	27.00	40.00	13.00
5	144.4600	36.88	peak	-12.01	24.87	40.00	15.13
6	154.1600	37.22	peak	-11.95	25.27	40.00	14.73

Condition: EN 55032 Class B 3m Radiation
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating


Polarization: Vertical
Power: AC 110V/60Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dB _{uV})	Detector	Corrected dB/m	Result (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)
1	30.000	35.40	QP	-3.49	31.91	40.00	8.09
2	45.5200	42.10	QP	-14.70	27.40	40.00	12.60
3	85.2900	47.40	QP	-17.03	30.37	40.00	9.63
4	113.4200	44.80	QP	-11.26	33.54	40.00	6.46
5	119.2400	45.80	QP	-10.65	35.15	40.00	4.85
6	128.9400	44.30	QP	-10.72	33.58	40.00	6.42

Condition: EN 55032 Class B 3m Radiation
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating


Polarization: Horizontal
Power: AC 230V/50Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dB _{UV})	Detector	Corrected dB/m	Result (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)
1	30.000	32.65	peak	-3.49	29.16	40.00	10.84
2	85.2900	38.55	peak	-17.03	21.52	40.00	18.48
3	102.7500	37.75	peak	-13.74	24.01	40.00	15.99
4	126.0300	39.57	peak	-10.58	28.99	40.00	11.01
5	160.9500	38.39	peak	-12.09	26.30	40.00	13.70
6	214.3000	38.84	peak	-13.78	25.06	40.00	14.94

Condition: EN 55032 Class B 3m Radiation
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating

Polarization: Vertical
Power: AC 230V/50Hz
Distance: 3m




No.	Frequency (MHz)	Reading (dB _{UV})	Detector	Corrected dB/m	Result (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)
1	35.8200	36.30	QP	-7.76	28.54	40.00	11.46
2	47.4600	48.61	peak	-15.66	32.95	40.00	7.05
3	85.2900	49.30	QP	-17.03	32.27	40.00	7.73
4	111.4800	45.60	QP	-11.71	33.89	40.00	6.11
5	118.2700	46.70	QP	-10.63	36.07	40.00	3.93
6	124.0900	45.00	QP	-10.46	34.54	40.00	5.46

Above 1G

Condition: EN 55032 Class B
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating


Polarization: Horizontal
Power: AC 110V/60Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dB _{UV})	Detector	Corrected dB/m	Result (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)
1	2717.500	47.27	peak	4.85	52.12	70.00	17.88
2	2717.500	26.54	AVG	4.85	31.39	50.00	18.61
3	3982.500	35.65	peak	9.10	44.75	74.00	29.25
4	3982.500	23.57	AVG	9.10	32.67	54.00	21.33
5	5985.000	34.92	peak	14.00	48.92	74.00	25.08
6	5985.000	22.84	AVG	14.00	36.84	54.00	17.16

Condition: EN 55032 Class B
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating


Polarization: Vertical
Power: AC 110V/60Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dB _B V)	Detector	Corrected dB/m	Result (dB _B V/m)	Limit (dB _B V/m)	Margin (dB)
1	2717.500	53.99	peak	4.85	58.84	70.00	11.16
2	2717.500	27.51	AVG	4.85	32.36	50.00	17.64
3	2782.500	48.37	peak	5.17	53.54	70.00	16.46
4	2782.500	25.68	AVG	5.17	30.85	50.00	19.15
5	5992.500	35.32	peak	14.04	49.36	74.00	24.64
6	5992.500	23.61	AVG	14.04	37.65	54.00	16.35

Condition: EN 55032 Class B
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating


Polarization: Horizontal
Power: AC 230V/50Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dB _{UV})	Detector	Corrected dB/m	Result (dB _{UV} /m)	Limit (dB _{UV} /m)	Margin (dB)
1	2785.000	43.97	peak	5.18	49.15	70.00	20.85
2	2785.000	25.68	AVG	5.18	30.86	50.00	19.14
3	3970.000	35.93	peak	9.08	45.01	74.00	28.99
4	3970.000	23.64	AVG	9.08	32.72	54.00	21.28
5	5987.500	35.37	peak	14.02	49.39	74.00	24.61
6	5987.500	23.67	AVG	14.02	37.69	54.00	16.31

Condition: EN 55032 Class B
EUT: AX3000 Whole Home Mesh Wi-Fi 6 System
Model: Mesh12X
Test Mode: Operating

Polarization: Vertical
Power: AC 230V/50Hz
Distance: 3m



No.	Frequency (MHz)	Reading (dB _B uV)	Detector	Corrected dB/m	Result (dB _B uV/m)	Limit (dB _B uV/m)	Margin (dB)
1	2555.000	45.18	peak	4.14	49.32	70.00	20.68
2	2555.000	32.69	AVG	4.14	36.83	50.00	13.17
3	2792.500	55.98	peak	5.20	61.18	70.00	8.82
4	2792.500	36.57	AVG	5.20	41.77	50.00	8.23
5	5982.500	34.81	peak	13.99	48.80	74.00	25.20
6	5982.500	23.64	AVG	13.99	37.63	54.00	16.37

3 – ELECTROSTATIC DISCHARGES IEC 61000-4-2


Measurement Uncertainty

U_{lab} (measurement uncertainty of lab) and U_{EN} (measurement uncertainty of EN 61000-4-2 and BS EN 61000-4-2) please refer to the following:

Parameter	U_{EN}	U_{lab}
Rise time t_r	$\leq 15\%$	15%
Peak current I_p	$\leq 7\%$	6.30%
Current at 30 ns	$\leq 7\%$	6.30%
Current at 60 ns	$\leq 7\%$	6.30%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test System Setup



Remark: ■ is the tip of the electrode

IEC61000-4-2 specifies that a tabletop EUT shall be placed on a non-conducting table which is 80 centimeters above a ground reference plane and that floor mounted equipment shall be placed on a insulating support approximately 10 centimeters above a ground plane. During the tests, the EUT is positioned over a ground reference plane in conformance with this requirement.

For tabletop equipment, a 1.6 by 0.8-meter metal sheet (HCP) is placed on the table and connected to the ground plane via a metal strap with two 470 k Ohms resistors in series. The EUT and attached cables are isolated from this metal sheet by *0.5-millimeter* thick insulating material. A Vertical Coupling Plane (VCP) grounded on the ground plane through the same configuration as in the HCP is used.

Test Standard

- EN 55035:2017+A11:2020(IEC 61000-4-2:2008)
- BS EN 55035:2017+A11:2020(IEC 61000-4-2:2008) *
- Test level 3 for Air Discharge at $\pm 8 \text{ kV}$
- Test level 2 for Contact Discharge at $\pm 4 \text{ kV}$

Test Level

Level	Test Voltage Contact Discharge (\pm kV)	Test Voltage Air Discharge (\pm kV)
1.	2	2
2.	4	4
3.	6	8
4.	8	15
X.	Special	Special

Performance criteria: B**Test Procedure****Air Discharge:**

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

Contact Discharge:

All the procedure shall be same as Section 8.3.1 of IEC 61000-4-2, except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

Indirect discharge for horizontal coupling plane:

At least 10 single discharges shall be applied to the horizontal coupling plane, at points on each side of the EUT. The discharge electrode positions vertically at a distance of 0.1m from the EUT and with the discharge electrode touching the coupling plane.

Indirect discharge for vertical coupling plane:

At least 10 single discharges shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m×0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

Test Data

Please refer to following tables:

Test Mode: Operating

Note:

Table 1: Electrostatic Discharge Immunity (Air Discharge)

Test Points Location	Test Level							
	-2 kV	+2 kV	-4 kV	+4 kV	-8 kV	+8 kV	-15 kV	+15 kV
Non-metallic Shell	A	A	A	A	A	A	/	/
DC Port	A	A	A	A	A	A	/	/
DC Cable	A	A	A	A	A	A	/	/
Seam	A	A	A	A	A	A	/	/
Button	A	A	A	A	A	A	/	/
Adapter	A	A	A	A	A	A	/	/

Table 2: Electrostatic Discharge Immunity (Direct Contact)

Test Points Location	Test Level							
	-2 kV	+2 kV	-4 kV	+4 kV	-8 kV	+8 kV	-8 kV	+8 kV
/	/	/	/	/	/	/	/	/





Table 3: Electrostatic Discharge Immunity (Indirect Contact HCP)

Test Points Location	Test Level							
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV
Front Side	A	A	A	A	/	/	/	/
Back Side	A	A	A	A	/	/	/	/
Left Side	A	A	A	A	/	/	/	/
Right Side	A	A	A	A	/	/	/	/

Table 4: Electrostatic Discharge Immunity (Indirect Contact VCP)

Test Points Location	Test Level							
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV
Front Side	A	A	A	A	/	/	/	/
Back Side	A	A	A	A	/	/	/	/
Left Side	A	A	A	A	/	/	/	/
Right Side	A	A	A	A	/	/	/	/

ESD Location Photo



Air Discharge:



Direct Contact:



4 – CONTINUOUS RADIATED DISTURBANCES IEC 61000-4-3


Measurement Uncertainty

U_{lab} (measurement uncertainty of lab) and U_{EN} (measurement uncertainty of EN 61000-4-3 and BS EN 61000-4-3) please refer to the following:

Parameter	U_{EN}	U_{lab}
Calibration process	1.88 dB	1.88 dB
Level setting	2.19 dB	2.19 dB

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test System Setup



Test Standard

EN 55035:2017+A11:2020 (IEC 61000-4-3:2006+A1:2007+A2:2010)
 BS EN 55035:2017+A11:2020 (IEC 61000-4-3:2006+A1:2007+A2:2010) *

Test Level

Level	Field Strength V/m
1.	1
2.	3
3.	10
X.	Special

Performance criteria: A

Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above the ground. The EUT is set 3 meters away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarizations of the antenna are set on test. Each of the four sides of EUT must be faced this transmitting antenna and measured individually. In order to judge the EUT performance, a CCD camera a laptop and a smartphone were used to monitor the EUT.

Test Data

Please refer to following tables:

Test Mode: Operating

Note:

Condition of Test	Remarks	
Field Strength	3 V/m (Test Level 2)	
RF Signal	1 kHz, 80% AM, sine wave	
Sweep Frequency Step	1%, logarithmic	
Dwell Time	1 Sec	

Table 1: Radiated RF-Electromagnetic Field Immunity

Frequency Range (MHz)	Front Side		Rear Side		Left Side		Right Side	
	VERT	HORI	VERT	HORI	VERT	HORI	VERT	HORI
80-1000	A	A	A	A	A	A	A	A

Table 2: Radiated RF-Electromagnetic Field Immunity

Spot Test (MHz)	Front Side		Rear Side		Left Side		Right Side	
	VERT	HORI	VERT	HORI	VERT	HORI	VERT	HORI
1800, 2600, 3500, 5000	A	A	A	A	A	A	A	A

Note: "A" stand for, during test, operate as intended no loss of function, no degradation of performance, no unintentional transmissions and after test, no degradation of performance, no loss of function, no loss of stored data or user programmable functions.

5 – CONTINUOUS CONDUCTED DISTURBANCES IEC 61000-4-6


Measurement Uncertainty

U_{lab} (measurement uncertainty of lab) and U_{EN} (measurement uncertainty of EN 61000-4-6 and BS EN 61000-4-6) please refer to the following:

Parameter	U_{EN}	U_{lab}
CDN calibration process	1.27 dB	1.27 dB
CDN test process	1.36 dB	1.36 dB

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Setup



Test Standard

EN 55035:2017+A11:2020 (IEC 61000-4-6:2008)

BS EN 55035:2017+A11:2020 (IEC 61000-4-6:2008) *

Test level 2 at 3 V (r.m.s.), 0.15MHz ~ 10MHz,

Test level 3-1 V (r.m.s.), 10MHz ~ 30MHz,

Test level 1 at 1 V (r.m.s.), 30MHz ~ 80MHz,

Test Level

Level	Voltage Level (r.m.s.) (V)
1	1
2	3
3	10
X	Special

Performance criteria: A

Test Procedure

- 1) Let the EUT work in test mode and test it.
- 2) The EUT are placed on an insulating support 0.1m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).
- 3) The disturbance signal described below is injected to EUT through CDN.
- 4) The EUT operates within its operational mode(s) under intended climatic conditions after power on.
- 5) The frequency range is swept from 150 kHz to 80MHz using 3V signal level, and with the disturbance signal 80% amplitude modulated with a 1 kHz sine wave.
- 6) Where the frequency is swept incrementally, the step size shall not exceed 1 % of the preceding frequency value. The dwell time of the amplitude modulated carrier at each frequency shall not be less than the time necessary for the EUT to be exercised and to respond, but shall in no case be less than 0.5 s.
- 7) Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

Test Data

Please refer to following tables:

Test Mode: Operating

Note:

Table 1: AC mains power input port

Frequency range: 150 kHz to 80 MHz
 Modulated: Amplitude 80%, 1kHz sine wave Unmodulated
 Dwell Time 1 Sec

Frequency(MHz)	Voltage Level	Pass	Fail
0.15-10	3V		
10-30	3V-1V	A	/
30-80	1V		


Table 2: Signal Port : RJ45

Frequency range: 150 kHz to 80 MHz
 Modulated: Amplitude 80%, 1kHz sine wave Unmodulated Other:
 Dwell Time 1 Sec

Frequency(MHz)	Voltage Level	Pass	Fail
0.15-10	3V		
10-30	3V-1V	A	/
30-80	1V		

6 – POWER FREQUENCY MAGNETIC FIELDS IEC 61000-4-8

Test Setup



Test Standard

EN 55035:2017+A11:2020&EN 55035:2017+A11:2020(IEC 61000-4-8:2009)
BS EN 55035:2017+A11:2020&EN 55035:2017+A11:2020(IEC 61000-4-8:2009) *

Test Level

Level	Magnetic Field Strength A/m
1	1
2	3
3	10
4	30
5	100
X.	Special

Performance criteria: A

Test Procedure

The EUT shall be subjected to the test magnetic field by using the induction coil of standard dimensions (1m*1m). The induction coil shall then be rotated by 90°in order to expose the EUT to the test field with different orientations.

Test Data

Not Applicable: The EUT do not contain PFMF sensitive component..

7 – ELECTRICAL FAST TRANSIENTS/BURST IEC 61000-4-4


Measurement Uncertainty

U_{lab} (measurement uncertainty of lab) and U_{EN} (measurement uncertainty of EN 61000-4-4 BS EN 61000-4-4) please refer to the following:

Parameter	U_{EN}	U_{lab}
Rise time t_r	6.20%	6.20%
Peak voltage value V_p	8.60%	8.60%
Voltage pulse width t_w	5.90%	5.90%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test System Setup



Test Standard

EN 55035:2017+A11:2020 (IEC 61000-4-4:2012)

BS EN 55035:2017+A11:2020 (IEC 61000-4-4:2012) *

AC mains: Test level 2 at 1 kV

Signal port: Test level 2 at 0.5 kV

Test Level

Open Circuit Output Test Voltage ±10%		
Level	On Power Supply Lines	On I/O (Input/Output) Signal data and control lines
1	0.5 kV	0.25 kV
2	1 kV	0.5 kV
3	2 kV	1 kV
4	4 kV	2 kV
X	Special	Special

Performance criteria: B

Test Procedure

The EUT was arranged for Power Line Coupling and for I/O Line Coupling through a capacitive clamp, where applicable. (Note: The I/O coupling test using a capacitive clamp is performed on the I/O interface cables that are longer in length than 3 meters.) A metal ground plane 2.4 meter by 2.0 meter was placed between the floor and the table and is connected to the earth by a 2.0 meter ground rod. The ground rod is connected to the test facility's electrical earth.

Test Data

Please refer to following tables:


Test Mode: Operating

Note:

Test Points		Test Level (kV)							
		+0.5	-0.5	+1.0	-1.0	+2.0	-2.0	+4.0	-4.0
<u>AC</u> mains power input ports	L	A	A	A	A	/	/	/	/
	N	A	A	A	A	/	/	/	/
	Earth	/	/	/	/	/	/	/	/
	L+N	A	A	A	A	/	/	/	/
	L + Earth	/	/	/	/	/	/	/	/
	N + Earth	/	/	/	/	/	/	/	/
	L+N+Earth	/	/	/	/	/	/	/	/
Signal ports	RJ45	A	A	/	/	/	/	/	/

8 – SURGES IEC 61000-4-5

Test System Setup



Test Standard

EN 55035:2017+A11:2020 (IEC 61000-4-5:2005)

BS EN 55035:2017+A11:2020 (IEC 61000-4-5:2005) *

AC Mains: L-N: Test level 2 at 1kV

Signal port : Test level 2 at 1kV

Test Level

Level	Open Circuit Output Test Voltage ±10%
1	0.5 kV
2	1 kV
3	2 kV
4	4 kV
X	Special

Performance criteria: B

Test Procedure

- 1) Provide disturbance signal described below is injected to EUT.
- 2) At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.
- 3) Different phase angles are done individually.
- 4) Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

Test Data

Please refer to following tables:

Test Mode: Operating

Note:

Table 1: AC mains power input port


Level	Voltage	Poll	Path	Phase Angle	Pass	Fail
1	0.5kV	+	L- N,	90	A	/
1	0.5kV	-	L- N	270	A	/
2	1kV	+	L- N	90	A	/
2	1kV	-	L- N	270	A	/

Table 2: RJ45 I/O Circuit and Lines

Level	Voltage	Poll	Path	Pass	Fail
1	0.5kV	±	Line-Ground	A	/
2	1kV	±	Line-Ground	A	/

9 –VOLTAGE DIPS AND SHORT INTERRUPTIONS IEC 61000-4-11

Test Setup



Test Standard

EN 55035:2017+A11:2020 (IEC 61000-4-11:2004)

BS EN 55035:2017+A11:2020 (IEC 61000-4-11:2004) *

Test levels and Performance Criterion

Test Level

Test Level	U2 (% Reduction)	Duration (Periods)	Performance Criteria
1	>95	0.5	B
2	30	25	C
3	>95	250	C

Test Procedure

- 1)The interruption is introduced at selected phase angles with specified duration.
- 2)Record any degradation of performance.

Test Data

Please refer to following tables:

Test Mode: Operating

B indicates that the power supply of the EUT was interrupted


Note: during the test, and the EUT was restarted. After the test, it can automatically return to normal use.

Table 1: Voltage Dips/Interruptions Test

U2 (% Reduction)	Td (Periods)	Phase Angle	N	Result
>95	0.5	0/90/180/270	3	A
30	25	0/90/180/270	3	A
>95	250	0/90/180/270	3	B

10 – HARMONIC CURRENT EMISSIONS

Test System Setup



Test Standard

EN IEC 61000-3-2:2019+A1:2021

BS EN IEC 61000-3-2:2019+A1:2021★

Test product class

Class A: - Balanced three-phase equipment

- Household appliances excluding equipment identified as class D
- Tools excluding portable tools
- Dimmers for incandescent lamps
- Audio equipment

Class B: - Portable tools

- Arc welding equipment, which is not professional equipment

Class C: - Lighting equipment

Class D: Equipment having a specified power less than or equal to 600w, of the following type:

- Personal computer and personal computer monitors
- Television receivers

Table 1 – Limits for Class A equipment

Harmonic order n	Maximum permissible harmonic current A
Odd harmonics	
3	2,30
5	1,14
7	0,77
9	0,40
11	0,33
13	0,21
$15 \leq n \leq 39$	$0,15 \frac{15}{n}$
Even harmonics	
2	1,08
4	0,43
6	0,30
$8 \leq n \leq 40$	$0,23 \frac{8}{n}$

Table 2 – Limits for Class C equipment

Harmonic order n	Maximum permissible harmonic current expressed as a percentage of the input current at the fundamental frequency %
2	2
3	$30 \cdot \lambda^*$
5	10
7	7
9	5
$11 \leq n \leq 39$ (odd harmonics only)	3

* λ is the circuit power factor

Table 3 – Limits for Class D equipment


Harmonic order n	Maximum permissible harmonic current per watt mA/W	Maximum permissible harmonic current A
3	3,4	2,30
5	1,9	1,14
7	1,0	0,77
9	0,5	0,40
11	0,35	0,33
$13 \leq n \leq 39$ (odd harmonics only)	$3,85 \frac{n}{13}$	See Table 1

Test Data

Not Applicable: The rated power of EUT is less than 75W.

11 –VOLTAGE FLUCTUATIONS AND FLICKER

Test System Setup



Test Standard

EN 61000-3-3:2013+A1:2019+A2:2021*

BS EN 61000-3-3:2013+A1:2019+A2:2021*

Flicker Test Limits :

The limits shall be applicable to voltage fluctuations and flicker at the supply terminals of the equipment under test, measured or calculated according to clause 4 under test conditions described in clause 6 and annex A. Tests made to prove compliance with the limits are considered to be type tests.

The following limits apply:

- the value of Pst shall not be greater than 1,0;
- the value of Plt shall not be greater than 0,65;
- the value of d(t) during a voltage change shall not exceed 3,3 % for more than 500 ms;
- the relative steady-state voltage change, dc, shall not exceed 3,3 %;
- the maximum relative voltage change dmax, shall not exceed
 - a) 4 % without additional conditions;
 - b) 6 % for equipment which is:
 - switched manually, or
 - switched automatically more frequently than twice per day, and also has either a delayed restart (the delay being not less than a few tens of seconds), or manual restart, after a power supply interruption.

Note: The cycling frequency will be further limited by the Pst and Plt limit. For example: a dmax of 6 % producing a rectangular voltage change characteristic twice per hour will give a Plt of about 0,65.

c) 7 % for equipment which is

- attended whilst in use (for example: hair dryers, vacuum cleaners, kitchen equipment such as mixers, garden equipment such as lawn mowers, portable tools such as electric drills), or
- switched on automatically, or is intended to be switched on manually, no more than twice per day, and also has either a delayed restart (the delay being not less than a few tens of seconds) or manual restart, after a power supply interruption.

In the case of equipment having several separately controlled circuits in accordance with 6.6,limits b) and c) shall apply only if there is delayed or manual restart after a power supply interruption; for all equipment with automatic switching which is energized immediately on restoration of supply after a power supply interruption, limits a) shall apply; for all equipment with manual switching, limits b) or c) shall apply depending on the rate of

switching. Pst and Plt requirements shall not be applied to voltage changes caused by manual switching. The limits shall not be applied to voltage changes associated with emergency switching or emergency interruptions.

Test Data

Please refer to following tables:

Short time (Pst):	10 min
Observation time:	120 min (12 Flicker measurement)
Test Mode:	Operating
Power Source:	AC 230V/50Hz
Test Result	PASS

Maximum Flicker results

	EUT values	Limit	Result
Pst	0.028	1.00	PASS
Plt	0.028	0.65	PASS
dc [%]	0.005	3.30	PASS
dmax [%]	0.365	4.00	PASS
dt [s]	0.000	0.50	PASS

EXHIBITA – EUT PHOTOGRAPHS

For photos in this section, please refer to report No.: DG2220216-04699E-02 EXHIBIT A.

EXHIBITB – TEST SETUP PHOTOGRAPHS

Conducted emissions_AC

Conducted emissions front View



Conducted emissions side View



Conducted emissions_ ISN

Conducted emissions front View-ISN



Conducted emissions side View



Radiated Emissions


Radiated Emissions Below 1GHz front View




Radiated Emissions Below 1GHz rear View



Radiated Emissions Above 1GHz front View




Radiated Emissions Above 1GHz rear View




ESD

Test Setup Photo View



RS

Test Setup Photo View




EFT

AC Port test Setup Photo View



Signal Port Test Setup Photo View



Dips

Test Setup Photo View



CS

AC Port test Setup Photo View



Signal Port Test Setup Photo View



Flicker

Test Setup Photo View



Surge

Test Setup Photo View



Signal Port Test Setup Photo View



DECLARATION OF SIMILARITY LETTER

SHENZHEN TENDA TECHNOLOGY CO., LTD.

ADD: 6-8 Floor, Tower E3, No. 1001, Zhongshanyuan Road, Nanshan District, Shenzhen, China.
518052

TEL: 86-755-27657098 FAX: 866-755-27657178
E-mail:cert@tenda.cn

DECLARATION OF SIMILARITY


Date: 2022-02-16

Dear Sir or Madam:

We, SHENZHEN TENDA TECHNOLOGY CO., LTD hereby declare that the product: AX3000 Whole Home Mesh Wi-Fi 6 System, model: MX12, EX12, EM12 is electrically identical with the model: Mesh12X by BACL(Dongguan) with the same electromagnetic emissions and which was tested electromagnetic compatibility characteristics.

A description of the differences between those models and that are declared similar are as follows:
They are the same product, and just the different of the model name , the rest are the same.

Please contact me should there be need for any additional clarification or information.



Best Regards,

Signature:

Printed Name: Shen Yue

Title: Engineer

*******END OF REPORT*******